INDEX

RUBBER CHEMISTRY AND TECHNOLOGY

VOLUME 47, 1974

AUTHOR INDEX

ABBOTT, T. P., C. JAMES, W. M. DOANE, AND C. R. RUSSELL, Injection molding of conventional formulations based on starch-encased powdered rubber (Abstract), (5)

ALLEN, G., J. S. HIGGINS, AND C. J. WRIGHT, Segmental diffusion in rubbers studied by neutron quasielastic incoherent scattering, (5)

ANDRIES, J. C., see SMITH, R. W., (1) 64

ANTKOWIAK, T. A., see KYKER, G. S., (1) 32

ARNOLD, C., JR., Development and characterization of EN-7—a ferric acetylacetonate catalyzed poly(butadiene)-based elastomer (Abstract), (2) 456

ARNOLD, P. M., "Joe C. Krejci", Charles Goodyear Medalist-1974, (2) G29

AVERILL, S. J. AND R. G. FULLER, Testing of Synthetic rubbers for cure properties (Abstract), (2) 475

——, Characterization of natural rubber for cure properties (Abstract), (2) 476

BAN, L. L., W. M. HESS, AND L. A. PAPAZIAN, New studies on carbon–rubber gel, (4) 858

BANERJEE, S., see BHOUMICK, S., (2) 251

——, see DAS, C. K., (2) 266

BANKS, S. A., W. G. DEPIERRI, D. F. KRUSE, AND L. SPENADEL, Painted and color pigmented EPDM for protective rubber applications (Abstract), (2) 454

BARANWAL, K. C. AND P. N. SON, Co-curing of EPDM and diene rubbers by grafting accelerators onto EPDM, (1) 88

BEATTY, J. R., The effects of oil on the adhesion of rubber, (1) 161

——, AND E. C. DALGLISH, A new tester for dynamic rubber-to-metal adhesion, (1) 188

——, see STUDEBAKER, M. L., (4) 803

BECKMAN, J. A., G. CRANE, E. L. KAY, AND J. R. LAMAN, Scrap tire disposal (Review), (3) 597

BERRY, D. D. AND F. V. MCMILLEN, The collection of efflux SiO_2 and its use as a filler in rubber compounding (Abstract), (5)

BHOUMICK, S. AND S. BANERJEE, Studies on MBT-accelerated sulfur vulcanization of natural rubber reinforced with carbon black, (2) 251

BLACKSHAW, G. C. AND I. M. KRISTENSEN, Blends of bromobutyl, EPDM, and natural rubber in light-colored compounds (Abstract), (5)

BLAAUW, L. P., see CLAGUE, A. D. H., (5)

BLAIR, E. A., Ambient temperature rotational molding of liquid thermoset polymer systems (Abstract), (5)

BOOKS, J. T., see WARD, T. C., (5)

BOONSTRA, B. B., Traction-abrasion relationships of tread compounds containing improved reinforcing carbon blacks (Abstract), (2) 467

——, E. M. DANNENBERG, AND F. A. HECKMAN, The effect of structure breakdown of carbon black on rubber properties, (5)

BOSISIO, R. G., see SCHWARZ, H. F., (2) 473

BOUSTANY, K., see CORAN, A. Y., (2) 396

BOWERMAN, H. H., E. A. COLLINS, AND N. NAKAJIMA, Tensile stress-strain and stress-relaxation behavior of raw elastomers using a high-speed tester, (2) 307

——, see NAKAJIMA, N., (2) 318

BRACHACZEK, W. AND W. R. PIERSON, Analytical method for measuring SBR tire debris in the environment, (1) 150

——, see PIERSON, W. R. (5)

BRUZZONE, M., A. MAZZEI, AND G. GIULIANI, Uranium catalysts for the synthesis of highly cis-tactic polydienes, (5)

BUCHANAN, R. A., W. M. DOANE, C. R. RUSSELL, AND W. F. KWOLEK, Starch xanthide reinforced styrene–butadiene rubber-compounding to reduce water sensitivity (Abstract), (5)

Bukowski, R. A., Rubber compound modifications to minimize the in-rubber degradation of polyester cord in truck tires (Abstract), (2) 478
Bullman, G. W., see Decker, G. E., (2) 477

Cantor, S. E., Room-temperature-vulcanizing adhesive system based on EPDM (Abstract), (2) 459
Cardina, J. A., Particle size determination of tire-tread rubber in atmospheric dusts, (4) 1005
Carlsson, D. J. and D. M. Wiles, Importance of singlet oxygen in degradation of rubbers and plastics, (4) 991
Carpenter, C. B., see Sollberger, L. E., (5)
Chappell, S. F. III, see Field, R. E., (2) 457
Charrier, J. -M., Large elastic deformation theories and unstable deformations of rubber structures—thin shells, (4) 788
Chirico, V. E., see Dizon, E. S., (1) 231
——, see Ulmer, J. D., (4) 729
Clague, A. D. H., J. A. M. van Broeckhoven, and L. P. Blaauw, ^{13}C nuclear magnetic resonance spectroscopy of polydienes, Microstructure of poly(butadiene), (5)
Claxton, W. E. and F. S. Conant, Direct analog simulation of hysteretic heat buildup in rubber, (4) 717
Coddington, D. M., see Hubbard, A. W., (5)
Collins, E. A., see Bowerman, H. H., (2) 307
——, see Nakajima, N., (2) 318, 333; (4) 778
Conant, F. S., see Claxton, W. E., (4) 717
Cooper, S. L., see Seymour, R. W., (1) 19
Coran, A. Y., K. Boustany, and P. Hamed, Short-fiber–rubber composites: the properties of oriented cellulose-fiber-elastomer composites, (2) 396
Corish, P. J. and B. D. W. Powell, Elastomer blends (Review), (3) 481
Cotten, G. R. and E. M. Dannenberg, A novel method for evaluation of carbon blacks and correlation with roadwear ratings (Abstract), (2) 467
Couderc, D., see Schwarz, H. F., (2) 473
Crane, G., see Beckman, J. A., (3) 597

Dalglish, E. D., see Beatty, J. R., (1) 188
Dall'Asta, Gino, Preparation and properties of polyalkenamers (Review), (3) 511
D'Amico, J. J., see Potts, K. T., (2) 289
Dannenberg, E. M., see Cotten, G. R., (2) 467
——, see Boonstra, B. B., (5)
Dannis, M. L., Rubber dust from normal wear of tires, (4) 1011
Danusso, F., see Szilagyi, L., (1) 1
Das, C. K. and S. Banerjee, Studies on dicumyl peroxide vulcanization of styrene–butadiene rubber in presence of sulfur and 2-mercaptobenzothiazole, (2) 266
Davison, Lucile S., Meeting papers, abstracts, (2) 454; (5)
Decker, G. E., G. W. Bullman, and R. D. Stiehler, Miniature dies and rotor for Mooney viscometer (Abstract), (2) 477
DePierri, W. G., see Banks, S. A., (2) 454
Derringer, G. C., Variable shear rate viscosity of SBR-filler-plasticizer systems, (4) 825
Devine, M. L., L. E. Whittington, C. W. Good, and R. J. Sperley, Mobility of extender oil in tires under service conditions, (1) 127
——, E. J. Weaver, W. H. Wade, and J. E. Gardner, Petroleum pitch as a plasticizer for SBR and SBR blends, (4) 837
Dizon, E. S., A. E. Hicks, and V. E. Chirico, The effect of carbon black parameters on the fatigue life of filled rubber compounds, (1) 231
Doane, W. M., see Abbott, T. P., (5)
——, see Buchanan, R. A., (5)
Dorosieva, V., see Vasilev, A., (5)
Doss, R. C., see Marrs, O. L., (2) 461
Downey, R. E., Sprayable adhesive systems (Abstract), (2) 465
Dunn, J. R., Review of unsolved problems in the protection of rubber against oxidative degradation, (4) 960

Eldred, R. J., Radiation curing of ethylene-propylene-diene elastomers, (4) 924
Erickson, D. E., Dependence of laboratory tire-cord adhesion on rubber properties, (1) 213

Faber, E. M., New thermoplastic polyurethane for injection molding—characteristics, processing, and uses (Abstract), (2) 470

FALENDER, J. R. AND C. M. MONROE, Elastomeric polyblends—structure–property relationships, (1) 57
FIELD, R. E., S. F. CHAPPELL III, AND W. J. MCKILLIP, Tire cord to rubber adhesion using aminimide structures (Abstract), (2) 457
FINDLEY, H. J., see MEIER, D. J., (2) 457
FIRKINS, J. L., Tire cord dip pick up by atomic absorption spectroscopy, (2) 448
FORSTER, M. J., see LEHMICKE, D. J., (5)
FOWLER, P. R., see SIMPSON, B. D., (2) 461
FRENSDORFF, H. K., Thermal diffusivity measurements on elastomers, (4) 849
FULLER, R. G., see AVERILL, S. J., (2) 475

GALIL-OGLY, F. A., see KRYUKOVA, A. B., (2) 282
GARDNER, J. E., see DEVINEY, M. L., (4) 837
GAVRILOV, V. M. AND A. G. SHVARTS, Dependence of the polymer–solvent interaction parameter of vulcanizates based on cis-1,4-poly(butadiene) on the type and concentration of vulcanizing agent, (2) 303.
GENT, A. N., Fracture mechanics of adhesive bonds, (1) 202
——, Force-deflection relations for a model air spring, (2) 384
GILINSKAYA, N. S., see KRYUKOVA, A. B., (2) 282
GIULIANI, G., see BRUZZONE, M., (5)
GOOD, C. W., see DEVINEY, M. L. (1) 127
GOTSHALL, W. W. AND R. F. WOLF, Reinforcing carbons from petroleum coke (Abstract), (2) 470
GRECHANOVSKII, V. A., I. YA PODDUBNYI, AND L. S. IVANOVA, Molecular structure and macroscopic properties of synthetic cis poly(isoprene), (2) 342
GREENBERG, D. H., see KUCKRO, G. W., (2) 477

HALL, J. C., see PRETTYMAN, C. E., (5)
HALL, W. E. AND A. J. KOPRA, The relative effects of various zinc oxides in rubber (Abstract), (5)
HAMED, P., see CORAN, A. Y., (2) 396
HECKMAN, F. A., see BOONSTRA, B. B., (5)
HELFAND, E., see TONELLI, A. E., (5)
HESS, W. M., see BAN, L. L., (4) 858
——, see ULMER, J. D., (4) 729
HEWITT, N. L. AND M. P. WAGNER, The role of silica in EPDM adhesion (Abstract), (2) 458
HICKS, A. E., see DIZON, E. S., (1) 231
HIGGINS, G. M. C., AND G. P. MCSWEENEY, The analysis of rubber vulcanizates—identification of amine residues from sulfenamide accelerators by thin layer chromatography, (5)
HIGGINS, J. S., see ALLEN, G., (5)
HILL, L. A., see KUCKRO, G. W., (2) 477
HOFMANN, W., Problems in waste rubber disposal (Abstract), (5)
HOLMAN, P. R., see WHITTINGTON, W. H., (5)
HOODBHOY, A. I., New dimension in automotive use of thermoplastic urethane elastomers (Abstract), (2) 471
HORVE, L. R., Theoretical study of the flow of highly viscous materials (Abstract), (2) 474
HOWARD, J. A., Autoxidation and antioxidants. Basic principles and new developments, (4) 976
HUBBARD, A. W. AND D. M. CODDINGTON, Laboratory test for studying factors affecting cord strike-through in tubeless tires (Abstract), (5)

IDE, Y., see WHITE, J. L., (5)
IONINA, N. V., see NEL'SON, K. V., (2) 357
IVANOVA, L. S., see GRECHANOVSKII, V. A., (2) 342

JAMES, C., see ABBOTT, T. P., (5)
JANZEN, J. AND G. KRAUS, A general correlation between treadwear and carbon black properties (Abstract), (2) 465
JENKS, W. P., Radial passenger tires with all glass cords (Abstract), (5)

KADUNCE, R. J., Carbon black dispersion utilising the AMEDA system (Abstract), (2) 469
KALFAYAN, S. H., R. RAKUTIS, AND R. H. SILVER, Chemical stress relaxation and other studies on styrene–butadiene rubber, (5)
KANE, J., see POTTS, K. T., (2) 289

KAPUR, R. S., J. L. KOENIG, AND J. R. SHELTON, Raman spectral studies of 2-mercaptobenzothiazole accelerator systems, (4) 911
KAY, E. L., see BECKMAN, J. A., (3) 597
KENDRICK, T. C. AND A. H. WARD, Block copolymers of poly (α-methylstyrene) and polydimethylsiloxane (Abstract), (2) 456
KIBLER, R. W., see LEHMICKE, D. J., (5)
KLINE, R. H., Polymerizable antioxidants in elastomers (Abstract), (5)
KOENIG, J. L., see KAPUR, R. S., (4) 911
KOPRA, A. J., see HALL, W. E., (5)
KRAUS, G., see JANZEN, J., (2) 465
KREJCI, J. C., The evolution of oil furnace blacks. Charles Goodyear medal address, (2) G32
KRESGE, E. N., see WILCHINSKY, Z. W., (4) 895
KRISTENSEN, I. M., see BLACKSHAW, G. C., (5)
KRUSE, D. F., see BANKS, S. A., (2) 454
KRYUKOVA, A. B., A. S. KUZ'MINSKII, N. S. CILINSKAYA, F. A. GALIL-OGLY, AND G. A. SAKINA, Radiation chemical conversions in fluorine containing elastomers under different γ-irradiation conditions, (2) 282
KUCKRO, G. W., D. H. GREENBERG, R. G. NEWBERG, AND L. A. HILL, Vulcanizable ethylene-acetate compounds (Abstract), (2) 477
KUMLER, P. R., see NAKAJIMA, N., (4) 778
KUZ'MINSKII, A. S., see KRYUKOVA, A. B., (2) 282
KWOLEK, W. F., see BUCHANAN, R. A., (5)
KYKER, G. S. AND T. A. ANTKOWIAK, Phosphonitrilic fluoroelastomers—a new class of solvent resistant elastomers with exceptional flexibility at low temperature, (1) 32

LAMAN, J. R., see BECKMAN, J. A., (3) 597
LAMOND, T. G., see SIRCAR, A. K., (1) 48
LANGEVIN, P. P., R. J. PAYNE, AND C. S. SHEPHARD, A dynamic rubber–cord composite adhesion and fatigue test, (1) 171
LAUTENSCHLAEGER, F. K. AND M. MYHRE, Observations on the crosslinking of natural rubber with nitrosophenols and diisocyanates, (1) 100
LEHMICKE, D. J., I. B. PRETTYMAN, R. W. KIBLER, AND M. J. FORSTER, Effects of moisture in composites of skim stock and polyester tire-cord (Abstract), (5)
LESHIN, R., A comparative study of three equivalent accelerator systems (Abstract), (5)
LEBRAS, JEAN "Charles Dufraisse", (1) G16
LINDLEY, P. B., Non-relaxing crack growth and fatigue in a non-crystallizing rubber, (5)

MARK, J. E., see YU, C. U., (5)
MARRS, O. L., R. P. ZELINSKI, AND R. C. DOSS, Adhesive properties of radial styrene–butadiene block copolymers (Abstract), (2) 461
MAZZEI, A., see BRUZZONE, M., (5)
MCKEOUGH, D., see POTTS, K. T., (2) 289
MCKILLIP, W. J., see FIELD, R. E., (2) 457
MCMILLEN, F. V., see BERRY, D. D., (5)
MCSWEENEY, G. P., see HIGGINS, G. M. C., (5)
MEDALIA, A. I., Filler aggregates and their effect on reinforcement, (2) 411
MEIER, J. L. AND H. J. FINDLEY, Current trends in rubber-to-metal bonding (Abstract), (2) 457
MEYERS, F. S. AND J. D. WENRICK, A comparison of tensile stress-strain data from dumbbell, ring, and oval specimens, (5)
MOGHE, S. R., Short fiber reinforcement of elastomers, (5)
MONROE, C. M. AND A. H. WARD, Organic-silicone block copolymers (Abstract), (5)
——, see FALENDER, J. R., (1) 57
MOORE, K. C., Advantages of thiocarbamyl-sulfenamide accelerators (Abstract), (5)
MORAND, J. L., Oxidation of poly(isoprene), (5)
MORAWSKI, J. C., see VOET, A., (4) 758, 765
MUKHERJEE, D. P., Stress-strain and stress birefringence studies on natural rubber, isomerized natural rubber, and synthetic poly(isoprene), (5)
MYHRE, M., see LAUTENSCHAEGER, F. K., (1) 100

NAKAJIMA, N., E. A. COLLINS, AND H. H. BOWERMAN, Master curve for tensile stress-strain behavior of amorphous elastomers at small and large deformations, (2) 318
—— AND E. A. COLLINS, Deformational behavior of rubber in variable speed Mooney rheometer, (2) 333

——, ——, KUMLER, P. R., Dynamic viscoelastic properties of raw butadiene-acrylonitrile elastomers, (4) 778
——, see BOWERMAN, H. H., (2) 307
NATHAN, J. B., JR., see PRICE, S. J., (2) 463
NEL'SON, K. V., G. T. TKACHENKO, AND N. V. IONINA, Study of orientational transformation of supramolecular structures on the surface of uniaxially stretched elastomers, (2) 357
NEWBERG, R. G., see KUCKRO, G. W., (2) 477

PAPAZIAN, L. A., see BAN, L. L., (4) 858
PATEL, R. D., see WHITE, J. L., (5)
PAYNE, R. J., see LANGEVIN, P. P., (1) 171
PEPPIATT, J., Trans-1, 4-butadiene sheeting—its use in orthopedics and other medical conditions (Abstract), (5)
PIERSON, W. R. AND W. BRACHACZEK, Airborne particulate debris from rubber tires, (5)
——, see BRACHACZEK, W., (1) 150
PINTER, P. E., see SIRCAR, A. K., (1) 48
PODDUBNYI, I. YA, see GRECHANOVSKII, V. A., (2) 342
POTTS, K. T., J. KANE, D. MCKEOUGH, AND J. J. D'AMICO, The synthesis and spectral characteristics of some nitrosoanilines and their possible mode of action as curing agents for various types of rubbers, (2) 289
POWELL, B. D. W., see CORISH, P. J., (3) 481
POWERS, E. J., A technique for evaluating the hysteresis properties of tire cords, (5)
PRETTYMAN, C. E. AND J. C. HALL, Multiple function computerized laboratory data acquisition system (Abstract), (5)
PRETTYMAN, I. B., see LEHMICKE, D. J., (5)
PRICE, S. J. AND J. B. NATHAN, JR., Pressure sensitive adhesive film characterization by accelerated aging (Abstract), (2) 463
PRZYBYLA, R. L., Preliminary studies of the feasibility of radiation vulcanization of silicone rubber, (2) 285

RAILSBACK, H. E. AND N. A. STUMPE, JR., Blends of medium vinyl poly(butadiene) with SBR rubbers (Abstract), (5)
RAKUTIS, R., see KALFAYAN, S. H., (5)
RICCO, T., see SZILAGYI, L., (1) 1
ROGERS, T. H. AND W. O. SASSAMAN, Applications of elastomeric urethanes in industrial products (Abstract), (2) 472
ROWE, F., JR., Environmental control in the manufacture of carbon black (Abstract), (5)
ROYAL, T. B., Reprocessed oils for the rubber industry (Abstract), (5)
RUSSELL, C. R., see ABBOTT, T. P., (5)
——, see BUCHANAN, R. A., (5)

SAKINA, G. A., see KRYUKOVA, A. B., (2) 282
SARACSAN, J. W., see STEPHENS, H. W., (2) 472
SASSAMAN, W. O., see ROGERS, T. H., (2) 472
SCHWARZ, H. F., R. G. BOSISIO, M. R. WERTHEIMER, AND D. COUDERC, Microwave curing of solid and expanded synthetic rubber compounds (Abstract), (2) 473
SEYMOUR, R. W. AND S. L. COOPER, Viscoelastic properties of polyurethane block polymers, (1) 19
SHELTON, J. R., The role of certain organic sulfur compounds as preventive antioxidants, (4) 949
——, see KAPUR, R. S., (4) 911
SHEPHARD, C. S., (1) 171
SHVARTS, A. G., see GAVRILOV, V. M., (2) 303
SILVER, R. H., see KALFAYAN, S. H., (5)
SIMPSON, B. D. AND P. R. FOWLER, Contact adhesives based on radial block copolymers of butadiene and styrene (Abstract), (2) 461
SIRCAR, A. K., T. G. LAMOND, AND P. E. PINTER, Effect of heterogeneous carbon black distribution on the properties of polymer blends, (1) 48
SKELTON, JOHN, Bending hysteresis losses in cord-rubber composites, (2) 376
SKOLNIK, L., Cord–rubber adhesion. A quantitative shear-adhesion test, (2) 434
SMITH, R. C. AND H. L. STEPHENS, Calorimetric studies of rubber oxidation (Abstract), (5)
SMITH, R. W. AND J. C. ANDRIES, New Methods for electron microscopy for polymer blends, (1) 64
SOLLBERGER, L. E. AND C. B. CARPENTER, Chlorinated poly(ethylene) elastomers (Abstract), (5)

Son, P. N., see Baranwal, K. C., (1) 88
Spenadel, L., see Banks, S. A., (2) 454
Sperley, R. J., see Deviney, M. L., (1) 127
Stephens, H. L., J. W. Saracsan, D. V. Vaidya, and D. S. Winkler, Room temperature cured glycol/dimer diisocyanate urethane elastomers (Abstract), (2) 472
——, see Smith, R. C., (5)
Stewart, C. W., Sr., Coagulation and film deposition from synthetic rubber latices (Abstract), (2) 455
Stiehler, R. D., see Decker, G. E., (2) 477
Studebaker, M. L. and J. R. Beatty, Effects of compounding on dynamic mechanical properties of rubber, (4) 803
Swarin, S. J. and A. M. Wims, Applications of derivative and integral thermogravimetry to analysis of rubber formulations, (5)
Szilagyi, L., T. Ricco, and F. Danusso, Characterization of viscoelastic behavior of stereoregular poly(isoprene)s by relaxation experiments, (1) 1

Taylor, R. D., Effect of alkyl group structure on cure characteristics of N,N-Dialkylthiocarbamyl-,N′, N′-dialkylsulfenamide accelerators, (4) 906
Tkachenko, G. T., see Nel'son, K. V., (2) 357
Tonelli, A. E. and E. Helfand, Elastically ineffective crosslinks in rubbers, (5)
Treloar, L. R. G., The elasticity and related properties of rubbers (Review), (3) 626
Troppe, F. G., Secondary treatment of waste water from synthetic rubber production, (4) 932

Ulmer, J. D., W. M. Hess, and V. E. Chirico, The effects of carbon black on rubber hysteresis, (4) 729

Vaidya, D. V., see Stephens, H. L., (2) 472
Van Broeckhoven, J. A. M., see Clague, A. D. H., (5)
Van Lierop, B., Hydrocarbon emissions in the rubber industry (Abstract), (5)
Vasilev, A. and V. Dorosieva, Stress relaxation of SBR vulcanizates with various crosslinking and modifying agents, (5)
Vickers, R. A., Elastomeric springs for seismic shock isolation, (5)
Voet, A. and J. C. Morawski, Adaption of the rheovibron to the measurement of dynamic properties at elongations up to sample rupture, (4) 758
——, ——, Dynamic mechanical and electrical properties of vulcanizates at elongations up to sample rupture, (4) 765

Wade, W. H., see Deviney, M. L., (4) 837
Wagner, M. P., Heat generation and rubber–filler coupling bonds, (4) 697
——, see Hewitt, N. L., (2) 458
Ward, A. H., see Kendrick, T. C., (2) 456
——, see Monroe, C. M., (5)
Ward, T. C. and J. T. Books, Spin-label investigations of polyurethane networks, (5)
Weaver, E. J., see Deviney, M. L., (4) 837
Weening, W. E., Aspects of adhesion of steel cord to rubber (Abstract), (2) 479
Wenghoefer, H. M., Environmental effects on RFL adhesion, (5)
Wenrick, J. D., see Meyers, F. S., (5)
Wertheimer, M. R., see Schwarz, H. F., (2) 473
White, J. L., Y. Ide, and R. D. Patel, Rheological and phase separation phenomena in the polymerization of styrene and rubber-styrene solutions (Abstract), (5)
Whittington, L. E., see Deviney, M. L., (1) 127
Whittington, W. H., M. E. Woods, and P. R. Holman, Powdered rubber technology VI. Energy analysis of powdered rubber processing (Abstract), (5)
Wilchinsky, Z. W. and E. N. Kresge, A quantitative test for ozone resistance of rubber vulcanizates, (4) 895
Wiles, D. M., see Carlsson, D. J., (4) 991
Wims, A. M., see Swarin, S. J., (5)
Winkler, D. S., see Stephens, W. L., (2) 472
Willett, P. R., Heat generation of tires due to the viscoelastic properties of elastomeric components, (2) 363
Wolf, R. F., see Gotshall, W. W., (2) 470
Woods, M. E., see Whittington, W. H., (5)
Wright, C. J., see Allen, G., (5)

Yu, C. U. and J. E. Mark, Specific solvent effects in swollen polymer networks, (5)

Zelinski, R. P., see Marrs, O. L., (2) 461

SUBJECT INDEX

Abrasion, see also tire wear
as a function of hardness, (2) 468
of tread compound, (2) 467
Abrasion resistance, effect of rubber-filler bonds, (4) 697
Abstracts, papers presented at meetings of the Rubber Division, (2) 454; (5) 1300
Accelerators, cure rate and, (4) 906
dialkylthiocarbamyl sulfenamides, (4) 906
effect of substituents on, (4) 906
various chemical structures, (4) 906
effect of ring size on, (4) 906
mechanism of, (5) 1303
2-morpholinodithiobenzothiazole and 2-morpholinothiobenzothiazole as, (5) 1304
new, (5) 1303
scorch properties, (4) 906; (5) 1303
of vulcanization, (4) 906
Acetaldehyde, formation during oxidation of poly(isoprene), (5) 1094
Acetic acid, formation during oxidation of poly(isoprene), (5) 1094
n-octyl ester, specific solvent effect on polydimethylsiloxane, (5) 1151
Acetone, formation during oxidation of poly(isoprene), (5) 1094
Adhesion, dynamic, (1) 171, 188
effect of cements on, (1) 188
effect of Nylon cord and dip, (1) 171
effect of temperature, (1) 171
failure mode, (1) 188
rubber to metal, (1) 188
effect of rotational speed on temperature, (1) 188
ten per cent life estimate, (1) 188
Weibull distribution, (1) 188
effect of humidity, (5) 1066
effect of modulus, (1) 161
effect of ozone, (5) 1066
effect of u v light, (5) 1066
to fabric, of natural rubber, (3) 511
of polypentenamer, (3) 511
failure locus, (5) 1066
H-value for tested tire, (2) 446
modified H-test, (2) 434
RFL for tire cord, (5) 1066
of rubber, effects of oil on, (1) 161
rubber to cord, (2) 434, 457
under dynamic conditions, (1) 171
dynamic vs static tests, (1) 171
effect of oil migration, (1) 127
effect of rubber properties on, (1) 213
rubber to metal, (2) 457
effect of aminimide structure, (2) 457
rubber to steel, (1) 171; (2) 479
rubber to steel cord, effect on tire performance, (1) 171
shear test, (2) 434
silicas in poly(ethylene co propylene co diene) for, (2) 457, 458
static, effect of cements on, (1) 188
failure mode, (1) 188
stress birefringence, (2) 434
to various fibers, (5) 1066
Adhesion testing, dynamic, (1) 171, 188
H-test of tire cord, (1) 213
static, (1) 188
strip tests of tire cord, (1) 213
Adhesive, block copolymer, (2) 461
polydimethylsiloxane, (2) 463
polyurethane, (2) 463
properties of radial block poly(butadiene co styrene), (2) 461
room temperature vulcanizing, (2) 458
sprayable, (2) 465
Adhesive bonds, and adhesive layer thickness, (1) 202
fracture mechanics of, (1) 202
hardness and, (1) 202
modes of stress to failure, (1) 202
shape of adhesive joint and, (1) 202
shear-stress and, (1) 202
tensile-stress and, (1) 202
tension and, (1) 202
Adhesive bond failure, adhesive shrinkage in, (1) 202
Adhesive joint strength, (1) 202
Adhesive shrinkage, in bond failure (1) 202
Adipic acid, esters, derivative thermogravimetry and gas chromatography, (5) 193
Aging, effect on adhesion of high-oil-content rubber, (1) 161
effect on dynamic properties, (4) 803
effect on stress strain of various rubbers, (4) 803
formation of carbonyl and hydroxyl groups during, (5) 1265
heats of activation of, (5) 1265
formation of conjugated polyenes in poly(isoprene) during, (5) 1094
of poly(butadiene), (3) 511
of poly(butadiene co styrene), (3) 511
of polypentenamer, (3) 511
sequence, (5) 1036
and spring stiffness, (5) 1039
study by infrared spectroscopy, (5) 1265
study by stress relaxation, (5) 1265
study by swelling, (5) 1265
Air pollution from tire wear, analysis of, (1) 150
Air spring, compressive load and spring height, (2) 384
force-deflection relations, (2) 384
mechanical instability, (2) 384
membrane tension and spring height, (2) 384

shear force and spring height, (2) 384
tilting torque and spring height, (2) 384
Alloocimene, see octa-2,6-triene, 2,6-dimethyl
Aluminum alkyls, as cocatalysts for ring-opening polymerization, (3) 511
Amines, identification by thin layer chromatography, (5) 1206
quenching of singlet oxygen by, (4) 976
Analysis, of amines by thin layer chromatography, (5) 1206
of bromine in engine exhaust, (5) 1275
of conjugated polyenes in poly(isoprene) by ferricyanide, (5) 1094
of lead in engine exhaust, (5) 1275
of ozone cracking, (4) 895
of plasticising oils by gas chromatography, (5) 1193
of rubber formulations by thermogravimetry, (5) 1193
for tire debris in air, (1) 150; (5) 1275
for zinc in tire dust, (5) 1275
Angle abrasion index, (2) 467
Aniline, N-(2,2-dinitropropyl)-N,4-dinitroso, synthesis, (2) 289
N-(2-methyl-2-nitropropyl)-N-nitroso, synthesis, (2) 289
nitroso, curing agents for rubbers, (2) 289
mass spectra, (2) 289
nmr spectra, (2) 289
spectral characteristics, (2) 289
synthesis, (2) 289
Antioxidants, addition of peroxide radicals to olefins and, (4) 976
rate data, (4) 976
and autoxidation, (4) 976
inhibited, (4) 976
uninhibited, (4) 976
bound, (4) 960; (5) 1306
chain breaking, (4) 949, 960, 976
critical concentrations, (5) 1300
effectiveness of, (5) 1306
and initiation of polymerization, (5) 1306
mechanism of action of, (4) 949, 976
organic sulfur compounds, as, (4) 949
oxidation half-wave potentials of phenolic, (4) 960
peroxides and, (4) 976
polymerizable, (5) 1306
preventive, (4) 949, 960, 976
prooxidant effect, (5) 1300
reviews of, (4) 949, 960, 976
singlet oxygen mechanism, (4) 991
storage aging, (4) 960
sulfur containing, (4) 949, 976
synergism, (4) 976
volatilization, (4) 960
Apparatus, capillary rheometer, (4) 778, 825
for dynamic rubber to metal adhesion, (1) 188
hysteresis measurement, (5) 1053
Instron environmental chamber for tire cord testing, (5) 1053
measurement of oxidation products of poly-(isoprene), (5) 1094
Mooney rheometer, (4) 778
neutron spectrometer, (5) 1127
Rheovibron, (4) 758, 778
errors from, (4) 758
operation of, (4) 758
test sled for spring testing, (5) 1039
Atomic absorption spectroscopy, (2) 448
tire-cord dip pickup by, (2) 448
with tracer additive, (2) 448
calibration, (2) 448
correlation with gravimetric method, (2) 448
Autoxidation, (4) 976

Benzene, *o*-dichloro, with oxygen to dissolve SBR vulcanizates, (1) 150
Benzene, 2,4-dichloromethyl, specific solvent effect on polydimethylsiloxane, (5) 1151
Benzothiazole, 2-(morpholinodithio), accelerator action of, (5) 1304
2-(morpholinothio), accelerator action of, (5) 1304
2-Benzothiazolinethione, accelerated sulfur vulcanization of natural rubber, (2) 251
accelerated sulfur vulcanization of poly-(butadiene co styrene), (2) 266
effect on crosslinking efficiency of dicumyl peroxide and sulfur, (2) 251, 266
effect on crosslinking efficiency of dicumyl peroxide, (2) 251
effect on decomposition rate of dicumyl peroxide, (2) 251
kinetics of consumption in vulcanization, (2) 251
Raman spectrum of, (4) 906
reaction with dicumyl peroxide, (2) 253, 266
trapping of, in retarded vulcanization, (1) 79
Best paper awards, (4) G 88; (5) G 110
Bias-ply passenger tires, hysteresis losses in, (1) 118
Biodegradation of tire scrap, (3) 597
of wastewater from synthetic rubber manufacture, (4) 932
Biographical sketches, Dufraisse, Charles, (1) G 16
Frensdorff, H. K., (5) G 109
Krejci, Joe C., (2) 32
O'Connor, F. M., (1) G 7
Biooxidation, wastewater from synthetic rubber production, (4) 932
Birefringence, dependence on stress, (3) 625; (5) 1234
strain function, (5) 1234
Blends of rubbers, adhesion to steel tire cord, (1) 171
carbon black distribution in, (1) 48
compatibility of components in, (3) 481
distribution of compounding materials in, (3) 481
effect on polymer properties, (3) 481
elastomer-plastic blends, (3)
electron microscopy of, (1) 64
hardening for electron microscopy, (1) 64
in light-colored compounds, (5) 1317

methods for characterization, (3) 481
methods for producing, (3) 481
microstructure of, (3) 481
natural rubber with poly(ethylene co propylene co diene), (4) 895
ozone resistance of, (4) 895
plastic-elastomer blends, (3) 481
poly(butadiene)-Chlorobutyl, (1) 48
poly(butadiene)-natural rubber, (1) 48
poly(butadiene)-poly(butadiene co styrene), (1) 48; (4) 858
poly(butadiene co styrene)-natural rubber, (1) 48
processability of, (3) 481
structural aspects of, (3) 481
structure-property relationships, (1) 57
Block copolymers, (5) 1304, 1311
blends, (3) 481
of poly(butadiene) and poly(styrene), (2) 461
poly(α-methylstyrene) and polydimethylsiloxane, (2) 456; (5) 1304
properties of, (5) 1304
polyurethane, (1) 19
Bonded rubber, (4) 729
carbon black concentration and, (4) 729
carbon-black structure effect, (4) 729
mixing and, (4) 729
Bound rubber, poly(butadiene co styrene) and carbon black, (2) 425, 467
and tire wear, (2) 467
Braking coefficient, (2) 467
as function of hardness, (2) 469
Bromobutyl rubber, microwave curing, (2) 473
in rubber blends, (5) 1317
Brass, effect of oil on adhesion to rubber, (1) 161
1,4-Butanediol, oxidation product of poly(isoprene), (5) 1094
2,3-Butanedione, oxidation product of poly(isoprene), (5) 1094
2-Butanone, 4-hydroxy, oxidation product of poly(isoprene), (5) 1094
2-Butenal, oxidation product of poly(isoprene), (5) 1094
1-Buten-2-one, oxidation product of poly(isoprene), (5) 1094
Butyl rubber, blends containing, (3) 481
chlorinated, tire liner compound from, (5) 1315
dynamic properties, (4) 803
effect of carbon-black concentration, (4) 803
hysteresis of, (4) 803
mixing hysteresis of, (4) 803
stiffness-hysteresis charts, (4) 803
thermal diffusivity, (4) 849
Butyrolactone, 4-methyl-4-vinyl, oxidation product of poly(isoprene), (5) 1094

C_1, values for polydimethylsiloxane, (5) 1151
C_2, values for polydimethylsiloxane, (5) 1151
ε-Caprolactam, effect on vulcanizate properties of poly(butadiene co styrene), (5) 1241
Carbon-13, nuclear magnetic spectra of poly(butadiene), (5) 1136
Carbon-14, labeling of oil in migration studies, (1) 127
Carbon black, aggregates, (2) 411; (5) 1082
anisometry, (2) 411
breakdown of, (2) 411; (5) 1082
dibutylphthalate test, (2) 411
dielectric form factor, (2) 411
effect on properties, (1) 231; (2) 424; (4) 729; (5) 1082
particle size, (2) 411; (5) 1082
radical distribution function, (2) 411
solid material per aggregate, (2) 411
structure, (2) 411
breakdown during mixing, (4) 858; (5) 1082
bonded rubber and, (4) 729
channel black, (2) G 33
collection, (2) G 38
concentration and dynamic properties, (4) 729
and crosslink density increase, (2) 251
degree of dispersion in rubber, (2) 469
dibutyl phthalate absorption, (5) 1082
function of milling, (5) 1082
scale of, (2) G 38, G 40
distribution of in polymer blends, (1) 48
ecology of manufacture, (5) 1308
effect of concentration on bonded rubber, (4) 858
effect on crack growth of tire tread compounds, (1) 231
effect of dynamic moduli, (4) 765, 825
effects on fatigue life of black-loaded rubber vulcanizates, (1) 231
effect on hysteresis, (4) 729
effect of mill-breakdown on rubber properties, (5) 1082
effect of pyrolysis on size of, (5) 1082
effect on shear viscosity, (4) 825
effect on thermal diffusivity, (4) 849
effect on vulcanization with dicumyl peroxide, (2) 251
and elastic modulus-strain amplitude function, (4) 729
electron microscopy, (2) G 38, 413; (4) 858; (5) 1082
feedstock, (2) G 39
FEF, (2) 37
gel with rubber, (4) 858
graphitized, (4) 858
manufacture and ecology, (5) 1308
morphology, (4) 729, 858; (5) 1082
network with rubber, estimation of, (4) 729
occluded rubber in, (2) 411
oil furnace black, (2) 411
pelletizing, (2) G 39
from petroleum coke, (2) 470
pH, (2) G 37
pressure-milling of, (5) 1082
production in U. S., (2) G 32
Quantimet measurement, (4) 858; (5) 1082

reinforcement of phosphonitrilic fluoroelastomers by, (1) 32
reinforcing blacks, (2) G 37
rubber bonded to surface of, (4) 858
rubber interaction with, (4) 858
rubber trapped by, (4) 858
sedimentation of, (5) 1082
shape factor, (4) 729
and shear modulus, (4) 825
size distribution, (5) 1082
effect of mixing on, (5) 1082
slow cure type, (2) G 37
SRF, semi-reinforcing furnace black, (2) G 39, 253
and strain distribution, (4) 729
surface area, (2) G 40; (4) 858; (5) 1082
from pyrolysis of tires, (3) 597
ultrasonic dispersion, (4) 858
in water; (5) 1082
unit spacing, (4) 729
viscous modulus and, (4) 729, 825
and viscous modulus-strain amplitude function, (4) 729
world-wide production in 1973, (2) G 32
Carcass compounding for adhesion to tire cord, (1) 213
Catalysts for polymerization, and abrasion resistance of poly(butadiene), (5) 1175
and crystallization half-times of poly(butadiene), (5) 1175
and heat generation, of poly(butadiene), (5) 1175
of polyalkenamers, (3) 511
alcohols and phenols for metathesis, (3) 511
cocatalysts for, (3) 511
Friedel-Crafts for metathesis, (3) 511
heterogeneous, (3) 511
homogeneous, (3) 511
Lewis acids and, (3) 511
Lewis bases and, (3) 511
ligand effects on, (3) 511
temperature effect on, (3) 511
three-component, (3) 511
advantages of, (3) 511
tungsten for ring-opening polymerization, (3) 511
Ziegler-Natta, for ring-opening polymerization, (3) 512
of poly(butadiene) from Uranium compounds and Lewis acids, (5) 1175
effect of aging time, (5) 1175
and tear strength of poly(butadiene), (5) 1175
Cellulose fibers, aspect ratio, (2) 396
electron micrograph of, (2) 396
in fiber-rubber composites, (2) 396
Chlorobutyl rubber, in blends, (1) 48; (3) 481
Chromatography, thin layer, identification of amine residues in vulcanizates by, (5) 1206
Cobalt tallate, effect on adhesion of rubber to steel, (1) 171
Composites, rubber-fiber, (2) 396
rubber-polyester tire cord, (5) 1314
rubber-short fiber, (5) 1074
rubber-tire cord, (2) 376
Compression set, of poly(butadiene), (3) 511
of poly(butadiene co styrene), (3) 511
of trans polypentenamer, (3) 511
of trans polypentenamer, (3) 511
Computer, analog, (4) 717
data acquisition by, (5) 1300
Conductance, specific, (4) 765
thermal, see Diffusivity, thermal
Corresponding states, (4) 778
Covulcanization, poly(ethylene co propylene co diene) and diene rubbers, (1) 88
Crack growth, non-relaxing conditions, (5) 1253
equation for, (5) 1253
static and dynamic components, (5) 1253
of tire tread compounds, (1) 231
of vulcanizates of poly(butadiene co styrene), (5) 1253
Creep, of fiber-rubber composites, (2) 396
of poly(chlorobutadiene), (2) 455
Crosslink density, determination by elastic modulus, (2) 285
determination by equilibrium tension, (2) 303
effect of crosslink type, (4) 803
effect of dicumyl peroxide, (2) 266
effect of methyl iodide, (2) 266
effect of stearic acid, (2) 266
effect of sulfur, (2) 266
effect of zinc oxide, (2) 266
and filler-rubber bonding, (4) 697
as a function of reaction time, (2) 251
heat generation and, (4) 697
hysteresis and, (4) 803
increase by SRF black
of natural rubber vulcanizates, (2) 251
of poly(butadiene co styrene) vulcanizates, (2) 266
stiffness-hysteresis effect, (4) 803
storage modulus and, (4) 803
Crosslinking, see also Vulcanization
efficiency of, (2) 251
and molecular weight between crosslinks, (2) 354
during stress relaxation of vulcanizates, (5) 1265
Crosslinks, elastically ineffective, (5) 1116
intramolecular, (5) 1116
Crotonaldehyde, see 2-Butenal
Crystallinity, of polyurethanes, (1) 19
Crystallization, half-times, (3) 511; (5) 1175
of polyalkenamers, (3) 511
cis-poly(butadiene), (2) 357
cis-poly(isoprene), (2) 342
of polypentenamer, (3) 511
rate of, (3) 511
on stretching of rubber, (2) 342, 357
Cure, see also Vulcanization and Crosslinking
characteristics of natural rubber, (2) 476
characteristics by oscillating disk rheometer, (2) 475
characteristics of poly(butadiene), (2) 475

characteristics of poly(butadiene co styrene), (2) 475
characteristics of poly(isoprene), (2) 475
Cure rate, see also Vulcanization
of polypentenamer, (3) 511
Cure time, of natural rubber, (2) 251
of poly(butadiene co styrene), (2) 266
Cyclization reactions, (3) 511
Cyclobutene, ring-opening polymerization of, (3) 511
Cyclododecene, ring-opening polymerization of, (3) 511
Cyclohexylamine, identification by thin layer chromatography, (5) 1206
N-Cyclohexylthio-*o*-benzoic sulfimide, retarder of vulcanization, (1) 79
N-Cylohexylthiophthalimide, retarder of vulcanization, (1) 79
Cyclo-1,5-octadiene, ring-opening polymerization of, (3) 511
of substituted, (3) 511
Cyclooctene, ring-opening polymerization of, (3) 511
methathesis with acyclic olefins, (3) 511
Cyclopentene, extraction process for isolation of, (3) 511
ring-opening polymerization of, (3) 511
bulk polymerization, (3) 511
copolymers from, (3) 511
cis-elastomer from, (3) 511
trans elastomer from, (3) 511
synthesis from piperylene, (3) 511

De Mattia flex tester, in study of carbon black filled vulcanizates, (1) 231
Dibutyl phthalate absorption, (4) 729, 858; (5) 1052
for carbon black, (2) 417
for estimating occluded rubber in carbon black, (2) 417
for silica, (2) 417
o-Dichlorobenzene, see Benzene, *o*-dichloro
2,4-Dichlorotoluene, see Benzene, methyldichloro
Dicumyl peroxide, vulcanization by,
crosslinking efficiency, (2) 251, 266
in presence of carbon black, (2) 251
in presence of MBT, sulfur, zinc oxide, and stearic acid, (2) 251, 266
effect of MBT on vulcanization rate constant, (2) 251, 266
kinetics of decomposition, (2) 251, 266
rate constants of curing by, (2) 251, 266
reaction with MBT, (2) 251, 266
vulcanization by, (1) 32; (2) 251, 266, 303; (3) 511; (4) 697; (5) 1265
vulcanization of natural rubber, (2) 251
vulcanization of poly(butadiene co styrene), (2) 266
Dielectric relaxation of rubber blends, (3) 481
Die swell of rubber blends, (1) 48
Differential scanning calorimetry, oxidation study by, (5) 1300
Differential thermal analysis, of poly(butadiene co acrylonitrile), (2) 308
of polyurethanes, (5) 1160
Diffusion, segmental, for various rubbers, (5) 1127
activation energies of, (5) 1127
Diffusivity, thermal, effect of carbon black on, (4) 849
errors in measurement, (4) 849
of fluoroelastomers, (4) 849
of poly(ethylene co propylene co diene), (4) 849
relative temperature coefficient, (4) 849
and specific heat, (4) 849
theory, (4) 849
and thermal conductivity, (4) 849
Diisocyanates, in vulcanization of natural rubber, (1) 100
in polyurethane formation, (1) 19; (5) 1160
Disposal, of scrap tires, (3) 597
of waste rubber, (5) 1307
Dithio bis morpholine, grafted on poly(ethylene co propylene co diene), (1) 88
in accelerator systems, (5) 1304
Disulfide, bis(benzothiazolyl), Raman spectrum of, (4) 906
Dithiotrichloromethanes, retarders of vulcanization, (1) 79
Doppler line broadening, (5) 1127
and diffusion coefficient, (5) 1127
temperature dependence, (5) 1127
Double bond scission, in ring-opening polymerization, (3) 511
Dufraisse, Charles, biography, (1) G 16
Dust from tire wear, analysis, (4) 1005, 1011; (5) 1275
airborne character, (5) 1275
atmospheric concentration, (5) 1275
bromine analysis and, (5) 1275
collection of, (4) 1005, 1011; (5) 1275
comparison to engine-exhaust particulates, (5) 1275
degradation in biosphere, (4) 1011
effect of road surface, (4) 1011
estimate of toxicity, (4) 1005
fate of, (5) 1275
fraction of annual tire wear, (5) 1275
fraction of total road dust, (5) 1275
lead analysis and, (5) 1275
micrographs of, (4) 1011
oxidation of, (4) 1011
particle size of, (4) 1005, 1011
physical appearance, (5) 1275
and severity of tire wear, (5) 1275
size distribution, (4) 1011; (5) 1275
tire dust in highway dust, (4) 1005; (5) 1275
and traffic patterns, (5) 1275
and vehicle size, (5) 1275
zinc analysis and, (5) 1275
Dynamic modulus, (4) 765; see also Modulus
effect of silica and carbon black, (4) 765
of poly(butadiene co acrylonitrile), (4) 778
Dynamic properties, see also Viscoelastic properties and carbon black concentration, (4) 729, 765
effect on adhesion to tire cord, (1) 171

effect of carbon black aggregates, (1) 231; (2) 424; (4) 729; (5) 1082
and electrical conductance, (4) 765
measurement of, (1) 1, 19, 48, 57, 118, 171, 188, 202, 213, 231; (2) 307, 318, 333, 363, 396, 411; (3) 511; (4) 697, 717, 729, 758, 765, 778, 803, 825; (5) 1039, 1053, 1082, 1175, 1253, 1265
mixing effect, (4) 803
of poly(butadiene co styrene), (2) 333
of trans polypentenamer, (3) 511
with Rheovibron, (2) 333, 368; (4) 758, 765
and strain-amplitude variation, (4) 729, 765
and temperature variation, (4) 729, 765

Ecology, carbon black manufacture and, (5) 1308
control of, (5) 1307, 1308
hydrocarbon emissions, (5) 1307
wastewater and, (4) 932
Elastic modulus, (4) 729, 765, 778, 803
effect of aging, (4) 803
and elongation, (4) 765
and specific conductance, (4) 765
and strain amplitude, (4) 765
Elasticity, neo-Hookean, (4) 788
Elasticity theory, (3) 625; (5) 1151
and crystallization, (3) 625
and glassy state, (3) 625
kinetic, (3) 625
thermodynamic consequences, (3) 625
mathematical, (3) 625
molecular, (3) 625
statistical, (3) 625; (5) 1151
and swollen vulcanizates, (5) 1151
Electrical properties of vulcanizates, (4) 765
Electron micrographs, (1) 57, 64; (2) 357, 411; (4) 858; (5) 1082
of blends, (1) 57
of carbon blacks, (2) 411; (4) 858; (5) 1082
Electron microscopy, of carbon-black aggregates, (2) 411; (5) 1082
of fiber-rubber composite, (2) 387
of fumed silica, (2) 411
of rubber blends, (1) 57, 64
of precipitated silica, (2) 411
of surface of stretched film, (2) 357
Electron spin resonance spectroscopy, (5) 1160
Energy losses in tires, mechanism of, (1) 118; (2) 363
Engine exhaust particles, (5) 1275
bromine analysis and, (5) 1275
lead analysis and, (5) 1275
zinc analysis and, (5) 1275
Entanglement of rubber molecules, (1) 1; (4) 697; (5) 1116
Enthalpy, of melting, poly(isoprene) and poly(butadiene), (5) 1175
contribution to polymerization, (3) 511
Entropy contribution, to elasticity, (3) 625
to polymerization, (3) 511
EPDM, see Poly(ethylene co propylene co diene)
Epichlorohydrin rubbers, (1) 32, 57
Epoxides, as activators of catalysts for ring-opening polymerization, (5) 1094
Ethanol, oxidation product of poly(isoprene), (5) 1094
Ethyl methacrylate, see Methacrylic acid, ethyl ester
Ethylidene norbornane, preparation of, (1) 88

Failure envelope of poly(butadiene co acrylonitrile), (2) 307
Fatigue, in dynamic adhesion testing, (1) 171, 188; (5) 1253
at rubber to metal bonds, (1) 171, 188
tension-bending, (2) 396
Fatigue life, of black-rubber vulcanizates, (1) 231
effects of carbon black parameters, (1) 231
effect of hysteresis around crack tip, (5) 1253
effect of strain range, (5) 1253
equation for, (5) 1253
at maximum and minimum tearing energies, (5) 1253
and minimum strain, (5) 1253
non-relaxing factor, (5) 1253
of vulcanizates of poly(butadiene co styrene), (5) 1253
tearing energy approach, (5) 1253
Fatigue testing, (1) 171, 188; (5) 1253
Ferric ferricyanide, oxidation of conjugated polyenes by, (5) 1094
Fibers, calculation of direction modulus in rubber, (5) 1066
mathematical model, (5) 1066
modulus of rubber composite, (5) 1066
orientation in rubber, (5) 1066
Fiber-rubber composite, creep, (2) 396
electron micrograph, (2) 396
of bonded and unbonded fiber, (2) 396
fatigue of, (2) 396
of oriented cellulose fiber, (2) 396
fiber orientation, (2) 396; (5) 1066
modulus, (2) 396; (5) 1066
solvent swelling, (2) 396
stress relaxation, (2) 396
tensile strength, (2) 396
ultimate elongation, (2) 396
Young's modulus, (2) 396
Filler-rubber bonding, (4) 697
Firestone flexometer, in rubber-cord adhesion testing, (1) 171
Flex cracking, see also Fatigue failure
of blends, (1) 48
of polypentenamer, (3) 511
Flory-Rehner equation, (4) 697; (5) 1265
Flow unit, supermolecular, (2) 333
Fluoroelastomers, thermal diffusivity, (4) 849
Fluorosilicone rubbers, (1) 32
Force-deflection, function for elastomeric springs, (5) 1039
Fourier transform, of Carbon-13 nmr spectra, (5) 1136
Fracture energy, in adhesive-bond failure, (1) 202

Fracture mechanics, of adhesive bonds, (1) 202
Free energy, Gibbs and Helmholz, (3) 625
Frensdorff, H. K., biographical sketch, (5) G 109
Fuel from tire scrap, (3) 597
Furan, 2-methyl, oxidation product of poly-(isoprene), (5) 1094
Furan, 2-methyl-2-vinyl-5-keto, oxidation product of poly(isoprene), (5) 1094

Gas chromatography, analysis of oxidation products of poly(isoprene) by, (5) 1094
of pyrolysis products of rubber blends, (3) 481
Gel permeation chromatography, of phosphonitrilic fluoroelastomers, (1) 32
of poly(butadiene co styrene), (4) 858
Gengrinovich plots, (4) 849
Glass tire-cord, adhesion to rubber, (1) 213
in radial tire construction, (5) 1318
Glass transition temperatures, of polyalkenamers, (3) 511
of polyurethanes, (5) 1160
Gough-Joule effect, (3) 625
Grafting, of accelerators on elastomers, (1) 88
Green strength, natural rubber, (2) 342
of poly(isoprene), (2) 342
of polypentenamer, (3) 511
Guth-Gold equation, (2) 411; (4) 729

Hardness, natural rubber vulcanizates, (2) 251
poly(butadiene co styrene) vulcanizates, (2) 266
silicone rubber vulcanizates, (2) 285
Heat generation, analog computer simulation, (4) 717
blends of rubbers, (1) 48, 88
effect of fillers, (4) 697
effect of tire design, (1) 118; (2) 363
effect of petroleum pitch, (4) 837
and loss compliance of tires, (2) 363
relationship to crosslinks, (4) 697
in rubber-filler bonding, (4) 697
temperature rise in tires and, (1) 118; (2) 363; (4) 717
in tires, (1) 118; (2) 363
Hexadecane, specific solvent effect on polydimethylsiloxane vulcanizates, (5) 1151
2,5-Hexanedione, oxidation product of poly-(isoprene), (5) 1094
5-Hexen-2-one, 6 methyl, oxidation product of poly(isoprene), (5) 1094
High speed tester, tensile stress strain behavior with, (2) 307, 318
stress relaxation behavior with, (2) 307
Hysteresis, see also Phase angle, tangent of and Heat generation
bending, (2) 376
of Butyl rubber, (4) 803
carbon black and, (4) 729, 803
in cord-rubber composites, (2) 376
apparatus for, (2) 376
and crosslink density, (4) 803
effect of crosslink type, (4) 803
mixing effect, (4) 803
orientational of polyurethanes, (1) 19
at propagating crack tip of vulcanizates, (5) 1253
in rolling tires, (1) 118; (2) 363
effect of tire design on, (1) 118; (2) 363
stress strain and stress birefringence, (5) 1234
tire cord, (5) 1053
temperature dependence, (5) 1053
Hydrogen bonding in polyurethane block polymers, (1) 19
Hydrogenated poly(butadiene)s, carbon-13 nmr of, (5) 1136

Incineration of tire scrap, (3) 597
Infrared absorbance, analysis of air for poly-(butadiene co styrene), (1) 150; (5) 1275
Infrared dichroism, in viscoelasticity studies, (1) 19
Infrared spectra, of blends, (3) 481
of polyalkenamers, (3) 511
of poly(butadiene co styrene) and oxidized poly(butadiene co styrene), (5) 1265
Injection molding, (5) 1311
Internal energy, contribution to elasticity, (3) 625
dependence on temperature and strain, (3) 625
Inverse Langevin function, in non-Gaussian statistical theory, (3) 625

Karrer plasticity, of gels, (2) 342
of poly (isoprene), (2) 342
Kinetic theory of rubber elasticity, (3) 625; (5) 1116, 1151

Latex blending, (3) 481
Legislation on scrap tire disposal, (3) 597
Levulinaldehyde, see Pentanal, 2-keto
Lewis acids, cocatalysts for preparation of polyalkenamers, (3) 511
cocatalysts for preparation of poly(butadiene), (5) 1175
Loss tangent, see Phase angle, tangent of, Heat generation, and Hysteresis
Low temperature flexibility, (1) 32
of rubber blends, (1) 57

Mass spectra, of nitrosoanilines, (2) 289
Master curve of shear viscosity of poly-(butadiene co acrylonitrile), (2) 318
modulus-time curve, (2) 318, 333
reduction scheme for non-linear behavior, (2) 318
in viscosity-shear rate form (2) 318
Mean square end-to-end distance of rubber molecules, (5) 1151
Mechanical blending, (3) 481
Mechanochemical blending, (3) 481
Medical applications of trans(butadiene), (5) 1309
Meetings, Rubber Division, (1) G 8; (4) 85
Melting point, poly(butadiene), (5) 1175
enthalpy, (5) 1175

equation for, (5) 1175
function of molecular weight, (5) 1175
function of elongation, (5) 1175
master curve, (5) 1175
Melting point of poly(isoprene), (5) 1175
enthalpy, (5) 1175
function of elongation, (5) 1175
Melting point of polypentenamer, (3) 511
2-Mercaptobenzothiazole, see 2-Benzothiazolinethione
Metathesis reactions, (3) 511
catalysts for, (3) 511
disproportionation, (3) 511
mechanisms, (3) 511
production of polyalkenamers, (3) 511
ring-opening polymerization, (3) 511
Methacrolein, oxidation product of poly(isoprene), (5) 1094
Methacrylic acid, ethyl ester, oxidation product of poly(isoprene), (5) 1094
Methacrylic acid, oxidation product of poly(isoprene), (5) 1094
Methacrylic acid, 1-propenyl ester, oxidation product of poly(isoprene), (5) 1094
Methacrylyl alcohol, oxidation product of poly(isoprene), (5) 1094
Methanol, oxidation product of poly(isoprene), (5) 1094
Methyl iodide, effect on sulfur vulcanizates of poly(butadiene co styrene), (2) 261
Methyl vinyl ketone, see 1-Butene-3-one
Microscopical analysis of blends, (3) 481
Microstructure, of polyalkenamers, (3) 511
of poly(butadiene)s, (5) 1175
of polypentenamer, (3) 511
Microwave curing, (2) 473
Migration of oil in tires, (1) 127
Mixing, effect on carbon black particles, (5) 1082
effect on distribution of carbon black in rubber blends, (1) 48
effect on molecular weight distribution of rubber, (4) 858
of powdered rubber, (5) 1312
economy of, (5) 1312
energy consumption, (5) 1312
and rubber breakdown, (4) 729, 858
effect on Butyl rubber, (4) 803
hysteresis and, (4) 803
Modulus, complex, (4) 778
crosslink effect, (4) 803
Modulus, dynamic, effect on tire hysteresis, (1) 118; (2) 363
of poly(butadiene co styrene) and effect of carbon blacks, (2) 425; (4) 729, 758, 765, 803
effect on adhesion of rubber to cord, (1) 161
effect of crosslinks, (4) 803
effect of rubber-filler bonds, (4) 697
effect of temperature, (4) 803
elastic and critical stress-strain, (4) 895
experiment compared to theory, (3) 625
of fiber-reinforced elastomers, (2) 396; (5) 1074
low strain, variation with specimen geometry, (5) 1213
of natural rubber vulcanizates, (2) 251
of poly(butadiene co styrene) vulcanizates, (2) 266
reduced, (1) 1
relaxation, (1) 1
shear, of poly(butadiene co styrene), (4) 837
temperature variation of polyurethane, (5) 1160
silicone rubber vulcanizates, (2) 285
effect of radiation dose, (2) 285
storage, see Viscous modulus and Complex modulus
storage, tension and compression, (4) 803
of swollen vulcanizates, (5) 1151
temperature reduction for, (2) 318
tensile, dependence on specimen geometry, (5) 1213
of poly(butadiene co styrene) vulcanizates, (2) 411
time curve, (2) 318
Young's, of fibers, (2) 396
Young's, of fiber-rubber composite, (2) 396
Molding, injection, (5) 1311
rotational, (5) 1311
Molecular weight of rubbers, in carbon-rubber gel, (4) 858
in carbon-rubber sol, (4) 858
between crosslinks, (2) 342
effect of mixing on, (4) 858
effect of rubber breakdown on, (4) 858
between entanglements, (1) 1
and ineffective crosslinks, (5) 1116
of phosphonitrilic fluoroelastomers, (1) 32
of polyalkenamers, (3) 511
effect of conversion, (3) 511
of poly(butadiene)s, (5) 1175
polyurethanes, (1) 19
reduction by mixing, (4) 858
and relaxation, (1) 1
Molybdenum, compounds as catalysts for ring-opening polymerization, (3) 511
Mooney rheometer, miniature dies and rotor, (2) 477
torque-time curve of poly(butadiene co styrene), (2) 333
variable speed, (2) 333
Mooney-Rivlin plots, (1) 127
Mooney viscosity, of gels as function of swelling, (2) 342
as function of gel content, (2) 342
limitation of, (2) 316
of poly(butadiene co acrylonitrile), (2) 307
of poly(isoprene), (2) 342
of sol fraction, (2) 342
of rubber blends, (1) 48
Morpholine, identification by thin layer chromatography, (5) 1206
Morpholine, 2,6-dimethyl, identification by thin layer chromatography, (5) 1206
Morphology, of blends, (3) 481
of polyalkenamers, (3) 511

of poly(butadiene)s, (2) 357
of polyurethanes, (1) 19
Multiply perturbed total internal reflection polarization spectroscopy, (2) 357
of stretched vulcanizates, (2) 357

Natural rubber, acceleration of vulcanization of, (2) 251; (5) 1304
adhesion to metal, (1) 171, 188
blend with poly(butadiene) and adhesion, (1) 171
cocuring with poly(ethylene co propylene co diene) grafted with accelerators, (1) 88
crystallization, (5) 1175, 1234
half-times of, (5) 1175
strain induced, (5) 1234
cure characteristics, (2) 476
dynamic adhesion to tire cord, (1) 171
effect of aging on elastic modulus, (4) 803
effect of aging on stress strain, (4) 803
effect of oil on adhesion, (1) 161
elastic modulus, (4) 803
elastomeric springs from, (5) 1039
in fiber-rubber composite, (2) 396
heat generation of filled and gum vulcanizates, (4) 697
heat resistant, (1) 100
hysteresis and elastic modulus, (4) 803
effect of aging and stress strain, (4) 803
effect of carbon black concentration, (4) 803
isomerized, (5) 1234
birefringent hysteresis, (5) 1234
microstructure, (5) 1234
stress-optical coefficient, (5) 1234
stress-strain hysteresis, (5) 1234
mechanism of vulcanization, with p-nitrosophenols and diisocyanates, (1) 100
with sulfur, (2) 251
molecular weight between entanglements, (1) 1
physical properties of vulcanizates, (2) 251
in polymer blends, (1) 64
reduced modulus, (1) 1
relaxation spectrum, (1) 1
in rubber blends, (1) 64; (5) 1317
scorch retarders in, (1) 79
springs from, (5) 1039
stress-birefringence, (5) 1234
stress-optical coefficient, (5) 1234
stress strain, (2) 251; (4) 803; (5) 1234
stress-strain curve, (2) 342
stress strain and specimen geometry, (5) 1213
thermal diffusivity, (4) 849
relative temperature coefficient, (4) 849
viscoelasticity of, (1) 1
vulcanization, (1) 100; (2) 251
Neoprene, see Poly(chlorobutadiene)

Network, carbon black-rubber, (4) 729
effect on viscoelasticity, (4) 729
theory of, (3) 626; (5) 1116, 1151
Network defects, (3) 625; (5) 1116
Network structure, definition, (3) 625
entropy of network, (3) 625
entropy of single chain, (3) 625
equivalent random link, (3) 625
imperfections, (3) 625
limited extensibility of chains, (3) 625
stress strain relations in shear and simple extension, (3) 625
Neutron scattering, (5) 1127
low energy motions of rubbers and, (5) 1127
inelastic, (5) 1127
Niobium, compounds for ring-opening polymerization, (3) 511
Nitrogen dioxide, effect on tire cord adhesion, (5) 1066
Non-linear behavior of poly(butadiene co acrylonitrile), (2) 307
reduction scheme, (2) 318
Nuclear magnetic resonance spectra, (2) 289; (3) 481; (5) 1127, 1136
of blends of rubbers, (3) 481
carbon-13, (5) 1136
relaxation of, (5) 1127
Nylon, tire-cord adhesion, (1) 161, 171, 213
in tire cords, (5) 1053
Nylon cord tires, hysteretic losses in, (1) 118

Occluded rubber, in carbon black aggregates, (2) 411; (4) 729, 858; (5) 1082
2,6-Octadienal, 2,6-dimethyl, oxidation product of poly(isoprene), (5) 1094
2,4,6-Octatriene, 2,6-dimethyl, reference standard for conjugated polyenes in poly(isoprene), (5) 1094
reaction with ferric ferricyanide, (5) 1094
Oil, carbon-14 labeled, (1) 127
determination by gas chromatography and thermogravimetry, (5) 1193
effect on adhesion of rubber, (1) 161
effect of diffusion on tear rate, (1) 127
effect on hysteresis, (1) 127
effect on strength, (1) 127
effect on tear energy, (1) 127
effect on tensile properties, (1) 127
effect of type on rubber-cord adhesion, (1) 161
Oil migration, into carcass of tires and effect on properties, (1) 127
effect of service conditions on, (1) 127
effect of temperature and time in tires, (1) 127
in tires in service, (1) 127
reprocessed, (5) 1309
from tire pyrolysis, (3) 547
Optical anisotropy as function of extension, (3) 625
temperature coefficient, (3) 625
Optical properties of blends, (3) 481
Orientation function, polyurethanes, (1) 19
elongation dependence, (1) 19

time dependence, (1) 19
Oxidation, apparatus for collection of products from poly(isoprene), (5) 1094
calorimetry of, (5) 1300
effect of conjugation in poly(isoprene), (5) 1094
measurement by differential scanning calorimetry, (5) 1300
of poly(isoprene), (5) 1094
Oxygen, absorption by poly(isoprene), (5) 1094
Oxygen, single state, hydroperoxide decomposition of, (4) 991
photochemical generation of, (4) 991
quenchers for, (4) 991
quenching rate constants, (4) 991
sensitizers for, (4) 991
from ozone, (4) 991
thermal generation of, (4) 991
Ozone, degeneration to singlet oxygen, (4) 991
effect on tire cord adhesion, (5) 1066
Ozone resistance of vulcanizates, (4) 895
of blend of natural rubber with poly(ethylene co propylene co diene), (4) 895
critical stress and, (4) 895
static and dynamic, (4) 895
stored energy density and, (4) 895

Pentanal, 2-keto, oxidation product of poly(isoprene), (5) 1094
Peroxide, see also Dicumyl peroxide
decomposition, filler-rubber bonding and, (4) 697
vulcanization of phosphonitrilic fluoroelastomers, (1) 32
Petroleum pitch, (4) 837
Phase angle, tangent of, carbon black effect, (4) 729
compression effect, (4) 803
of poly(butadiene co styrene), (4) 729
temperature function, (4) 729, 803
tension effect, (4) 80-
Phenol, 2,6-di-t-butyl-p-nitroso with diisocyanates in vulcanization of natural rubber, (1) 100
Phenomenological theories of rubber elasticity, alternate form of representation, (3) 625
for compressible rubbers, (3) 625
deviation from statistical theory, (3) 625
form of stored energy function, (3) 625
general stress-strain relations, (3) 625
normal stresses in shear, (3) 625
Ogden's theory, (3) 625
particular stress-strain relationships in extension and shear, (3) 625
Rivlin's large deformation theory, (3) 625
torsion of cylinder, (3) 625
Phosphonitrolic fluoroelastomers, (1) 32
molecular weight of, (1) 32
rheology of, (1) 32
Photoelasticity, effect of swelling on stress-optical coefficient, (3) 625
equivalent random link, comparison with non-Gaussian theory, (3) 625
experimental dependence of birefringence on stress, (3) 625
network theory, (3) 625
non-Gaussian theory, (3) 625
stress-optical coefficient, (3) 625
temperature coefficient of optical anisotropy, (3) 625
theoretical conclusions, (3) 625
Phthalic acid, cyclohexylthioimide, as scorch retarder, (1) 79
Phthalic acid, N-(N,4-dinitrosoanilinomethyl) imide, synthesis, (2) 290
Polyalkenamers, (3) 511
polyoctenamer, (3) 511
polypentenamer, (3) 511
preparation, (3) 511
properties, (3) 511
structure, (3) 511
synthesis, (3) 511
metathetical, (3) 511
non-metathetical, (3) 511
Poly(butadiene), abrasion resistance, (5) 1175
absence of vinyl groups in, (3) 511
blend, tire properties of, (5) 1302
in blends, (3) 481
block, (5) 1310
carbon-13 nuclear magnetic spectra, (5) 1136
microsturcture and, (5) 1136
of hydrogenated, (5) 1136
cis-trans linkages in, (5) 1136
copolymerized antioxidants in, (5) 1306
copolymerization with styrene, block, (5) 1310
critical concentration of antioxidants, (5) 1300
crosslinker with alkyl phenol-formaldehyde oligomers, (2) 303
crystallization half-times, (5) 1175
temperature and, (5) 1175
strain ratio and, (5) 1175
crystallization rate, (3) 511
crystallization temperature, (5) 1175
crystallization, variation with polymerization catalyst, (5) 1175
cure characteristics, (2) 477
in elastomer blends, (1) 64, 171
adhesion of, (1) 171
enthalpy of melting, (5) 1175
equilibrium phase diagram, (5) 1310
fractionation, (5) 1175
heat generation of vulcanizates, (5) 1175
hydrogenated, chemical shifts of C-13 nmr, (5) 1136
improvement of belting with, (5) 1302
melting point of, (3) 511; (5) 1175
microstructure, (5) 1175
molecular weight distribution, (5) 1175
oil-addition conditions, (5) 1302
oxidation, (5) 1300
enthalpies, (5) 1300
polymerization kinetics, (5) 1175

polymer-solvent interaction parameter of vulcanizates, (2) 303
processability, (5) 1175
from ring-opening polymerization, (3) 511
sequence distribution of cis-trans units, (5) 1136
stereoregular synthesis, (5) 1175
Lewis acids as cocatalysts for, (5) 1175
uranium compounds as catalysts, (5) 1175
stress strain of vulcanizates, (5) 1175
tear strength, (5) 1175
thermal diffusivity, (4)
toluene diisocyanate end-capped, (2) 456
trans, medical application, (5) 1309
unfilled vulcanizates, (2) 357
uranium/Lewis acid ratio, effect on rubber conversion, (5) 1175
vinyl, (5) 1302
blend with cis poly(butadiene), tire properties of, (5) 1302
blend with poly(butadiene co styrene), (5) 1302
vulcanization mechanism, (4) 906
Poly(butadiene co acrylonitrile), braking force coefficient, (2) 467
bound antioxidants in, (5) 1306
copolymerized antioxidants in, (5) 1306
dynamic properties, (4) 778
in fiber-rubber composition, (2) 408
injection molded extrudates, (5) 1311
microwave curing, (2) 473
modulus-time curve, (2) 323
Mooney viscosity, (2) 308
powdered, (5) 1312
mixing economy, (5) 1312
stress-strain behavior, (2) 307
stress-strain master curve, (4) 778
stress-strain and specimen geometry, (5) 1213
stress relaxation, (2) 307
thermal diffusivity, (4) 849
thermogravimetry of, (5) 1193
viscoelasticity, (4) 778
viscosity-shear rate curve, (2) 325
Poly(butadiene co acrylonitrile co antioxidant), (5) 1306
Poly(butadiene co styrene), accelerators of sulfur vulcanization of, (2) 266; (4) 906; (5) 1304
aging effect on carbon black-rubber gel, (4) 858
aging and stress strain of, (4) 803
aging and dynamic properties, (4) 803
in air, determination of tire wear debris (1) 150
analysis relative to tire dust, (4) 1005; (5) 1275
in blends, (1) 48; (3) 481
block, (5) 1311
bound rubber, (2) 425, 467
carbon black filled, (1) 48, 127, 213, 231 (2) 411; (4) 697, 729, 765, 803, 825, 837, 858; (5) 1082, 1253, 1265
carbon black and viscoelasticity, (4) 697, 729, 765, 803, 825
carbonyl group and hydroxyl group formation oxidative aging, (5) 1265
chemical stress relaxation of vulcanizates of, (5) 1265
aging and, (5) 1265
continuous and temperature effect, (5) 1265
effect of crosslink density, (5) 1265
heat of activation, (5) 1265
in nitrogen and air, (5) 1265
oxidative aging, (5) 1265
rate constants of oxidative aging, (5) 1265
temperature effect, (5) 1265
copolymerized antioxidants in, (5) 1306
crack growth of vulcanizates of, (5) 1253
critical concentrations of antioxidants, (5) 1300
crosslink density of (2) 266; (4) 803; (5) 1265
cure characteristics, (2) 475
debris from tire wear, (1) 150; (4) 1005, 1011; (5) 1275
dynamic properties, (4) 697, 729, 765, 803, 825
effect of carbon black morphology on breakdown of, (4) 858
effect of mill-breakdown of carbon black on properties of, (5) 1082
effect of mixing with black on molecular weight distribution, (4) 858
effect of petroleum pitch, (4) 825
effect of various fillers, (4) 803, 825
elastic modulus, (4) 729, 765, 803
enthalpies of oxidation, (5) 1300
equilibrium phase diagram, (5) 1310
fatigue life of vulcanizates of, (1) 231; (5) 1253
effect of strain range, (5) 1253
equation for, (5) 1253
and minimum and maximum tearing energy, (5) 1253
non-relaxing factor, (5) 1253
tearing energy, (5) 1253
in fiber-rubber composites, (2) 399
fraction of total road dust, (5) 1275
free sulfur in vulcanizates, (2) 266
hysteresis of, (4) 729, 803
hysteresis and elastic modulus, (4) 803
effect of carbon black concentration, (4) 803
infrared spectra of oxidized vulcanizates of, (5) 1265
injection molded extrudates, (5) 1311
microwave curing, (2) 473
modulus-time curve, (2) 333
NBS standard, (2) 333
network with carbon black, (4) 729
oxidation and oxidation enthalpies, (5) 1300
radial block copolymer, (2) 461
relaxation times, (5) 1241
effect of acceleration, (5) 1241

effect of ε-caprolactam, (5) 1241
resin cosslinking of, (5) 1241
in roadside topsoil, (5) 1275
in rubber blends, (1) 64
scorch safety, (4) 906
shear modulus, (4) 837
shear rate viscosity, (4) 825
equations for, (4) 825
silica filled, (4) 697, 803, 825
viscosity of, (4) 825
starch xanthide reinforcement, (5) 1313
water sensitivity of, (5) 1313
storage modulus, (4) 803
stress relaxation of vulcanizates, (5) 1241
tan δ of, (4) 729
tearing energy, (5) 1253
thermal diffusivity, (4) 849
tire wear, (2) 467
traction-abrasion of tires of, (2) 467
treads and fatigue life, (1) 231
viscoelastic properties, (4) 729
viscosity-shear rate curve, (2) 333
viscous modulus-strain amplitude function, (4) 729
vulcanization, (2) 266
vulcanization by dicumyl peroxide and sulfur, (2) 266
vulcanization mechanism, (2) 266
Poly(butadiene co styrene co antioxidant), (5) 1306
Poly(chlorobutadiene), in blends, (1) 48
creep measurement, (2) 455
coagulation and film deposition from latexes, (2) 455
in fiber-rubber composites, (2) 408
thermal diffusivity, (4) 849
Poly(dichlorophosphazene), (1) 32
Polydimethylsiloxane, activation energy of segmental motion, (5) 1127
in blends, (1) 57
block copolymer with poly(α-methylstyrene), (2) 456
C_1 and C_2 (Mooney constants) values of, (5) 1151
solvent variation and, (5) 1151
diffusion coefficient, (5) 1127
temperature dependence, (5) 1127
phenyl-methyl substitution, (2) 287
pressure-sensitive adhesive, (2) 463
radiation crosslinking, (2) 285; (5) 1151
radiation vulcanizates of, (5) 1151
relaxation-mechanical, dielectric, and nmr, (5) 1127
specific solvent effects, (5) 1151
trifluoropropyl, (2) 287
vinyl content, (2) 287
Polydecenamer, (3) 511
Polydodecenamer, (3) 511
Polyenes, conjugated, (5) 1094
disappearance during aging of poly(isoprene), (5) 1094
formation during aging of poly(isoprene), (5) 1094
location in poly(isoprene), (5) 1094
Poly(epichlorohydrin), bonding to metal, (2) 457
Polyester tire cord, adhesion to rubber, (1) 161, 171
effect of oil on, (1) 161
Polyether urethane, block polymers, (1) 19
Poly(ethyl acrylate), in blends, (1) 57
Poly(ethylene), carbon-13 nmr of, (5) 1136
stress optical coefficient, (3) 625
Polyethylene, chlorinated, (5) 1301
blends of, (5) 1301
chlorination of, (5) 1301
Poly(ethylene co propylene) in blends, (3) 481
polymer-solvent interaction parameter, (2) 303
Poly(ethylene co propylene co dicyclopentadiene), cocuring with diene rubbers, (1) 88
Poly(ethylene co propylene co diene), aging and stress strain, (4) 803
blend with chlorinated poly(ethylene), (5) 1300
blend with natural rubber, ozone resistance, (4) 895
bonding to metal, (2) 457
bonding to RFL, (2) 458
cocuring with diene rubbers, (1) 88
curing of, (4) 924
curing aids for, (4) 924
effect of aging on elastic modulus and stress strain, (4) 803
effect of polymer type on adhesion, (2) 459
elastomeric spring from, (5) 1039
grafted with accelerators, (1) 88
radiation curing, (4) 924
for room-temperature-vulcanizing adhesive, (2) 459
in rubber blends, (1) 64; (4) 895; (5) 1300, 1317
springs from, (5) 1039
stiffness-hysteresis charts, (4) 803
thermal diffusivity in, (4) 849
thermogravimetry of, (5) 1193
trimethylol trimethacrylate as cocuring monomer, (4) 924
Poly(ethylene co propylene co 5-ethylidenenorbornene), (2) 454
cocuring with diene rubbers, (1) 88
painting and pigmenting of, (2) 454
Poly(ethylene co vinyl acetate), in fiber-rubber composite, (2) 408
vulcanizable, (2) 477
Poly(ethylene oxide), activation energy of segmental motion, (5) 1127
diffusion coefficient of, (5) 1127
temperature dependence, (5) 1127
neutron scatter of, (5) 1127
Polyethylene terephthalate, in tire cords, (5) 1053
Poly(isobutylene), activation energy of segmental motion, (5) 1127
diffusion coefficient, (5) 1127
temperature dependence, (5) 1127
neutron scatter of, (5) 1127

relaxation—mechanical, dielectric, and nmr, (5) 1127
Poly(isoprene), adhesion of, (1) 161, 171; (3) 511
aging, (5) 1094
in blends, (3) 481
birefringence, (5) 1234
cis-1,4 content, (2) 342
conjugated polyenes in, (5) 1094
formation and disappearance during aging, (5) 1094
crystallization, (5) 1234
half-times, (3) 511
strain-induced, (5) 1234
cure characteristics, (2) 475
dynamic adhesion. (1) 161, 171
effects of oil on adhesion, (1) 161
entanglement of molecules of, (1) 1
intrinsic viscosity of sol fraction, (1) 1; (2) 342
Karrer plasticity, (2) 342
mechanical degradation, (2) 342
microstructure, (5) 1234
modulus-time curves, (1) 1
molecular entanglement, (1) 1
molecular weight between crosslinks, (1) 1; (2) 342
molecular weight distribution, (2) 342
molecular weight between entanglements, (1) 1
molecular weight of sol and gel fraction, (2) 342
Mooney viscosity, as function of gel content, (2) 342
of gels as function of gel swelling index, (2) 342
of sol fraction, (2) 342
temperature function, (3) 511
network theory, (5) 1116
origin of gel particles, (2) 342
oxidation of, (5) 1094
oxidation products of, (5) 1094
oxygen absorption of, (5) 1094
processability, (2) 342
prooxygen effect, (5) 1094
quasi stable network, (2) 342
reaction with singlet oxygen, (4) 991
relaxation of, (1) 1
spectrum, (1) 1
sedimentation diagrams, (2) 342
shear modulus, (1) 1
size of gel particles, (2) 342
stress birefringence, (5) 1234
hysteresis of, (5) 1234
stress-optical coefficient, (3) 625; (5) 1234
stress-strain, (2) 342; (5) 1234
hysteresis, (5) 1234
supermolecular structure, (1) 1; (2) 342
swelling index of gel fraction, (2) 342
tack of, (3) 511
test for dynamic adhesion, (1) 171
volatile oxidation products, (5) 1094
gas chromatography of, (5) 1094
Polymer-solvent interaction parameter of poly(butadiene)s, (2) 303
Polymerization, ring-opening, (3) 511
cis-trans equilibria, (3) 511
control of cis-trans ratio, (3) 511
conversion, (3) 511
catalyst-activator effect, (3) 511
cross metathesis, (3) 511
of cycloolefins, (3) 511
enthalpy of, (3) 511
entropy of, (3) 511
translational, vibrational, and torsional, (3) 511
mechanistic details, (3) 511
molecular weight regulation, (3) 511
α-olefins and, (3) 511
rate of, (3) 511
stereoregulation, (3) 511
Polymethylphenylsiloxane, activation energy of segmental motion, (5) 1127
diffusion coefficient, (5) 1127
temperature dependence, (5) 1127
neutron scatter of, (5) 1127
Poly(α-methylstyrene), block copolymer with polydimethylsiloxane (2) 456
Polyoctenamer, aging, (3) 511
chain conformation, (3) 511
crystallization half-times, (3) 511
temperature variation of, (3) 511
enthalpy of fusion, (3) 511
entropy of fusion, (3) 511
glass transition temperature, (3) 511
infrared molar absorptivities, (3) 511
oil extended vulcanizate, (3) 511
physical properties of vulcanizates, (3) 511
polymerization, ring-opening, (3) 511
processing, (3) 511
vulcanization, (3) 511
vulcanizate properties, (3) 511
Polypentenamer, adhesion to fabric, (3) 511
aging, (3) 511
in blends, (1) 64
chain conformation, (3) 511
compounding, (3) 511
compression set and temperature, (3) 511
control of microstructure, (3) 511
copolymers of, (3) 511
crystallization, half-times, (3) 511
cure rate, (3) 511
temperature effect, (3) 511
dynamic properties, (3) 511
enthalpy of fusion, (3) 511
entropy of fusion, (3) 511
flex cracking, (3) 511
glass transition temperature, (3) 511
hardness (Shore A) as function of temperature, (3) 511
infrared absorption spectrum, (3) 511
infrared molar absorptivities, (3) 511
molecular weight distribution, (3) 511
Mooney viscosity and temperature dependence, (3) 511
oil extended vulcanizates, (3) 511
physical properties of vulcanizates, (3) 511
polymerization, ring-opening, (3) 511
processing, (3) 511
rebound resilience, (3) 511

reversion of vulcanization, (3) 511
Rheometer curves, (3) 511
stress-strain, effect of strain rate on, (3) 511
effect of temperature on, (3) 511
tack, (3) 511
vulcanization, (3) 511
vulcanizate properties, (3) 511
Poly(propylene oxide), activation energy of segmental motion, (5) 1127
deuterated, (5) 1127
diffusion coefficient, (5) 1127
temperature dependence, (5) 1127
neutron scattering, (5) 1127
relaxation-mechanical, dielectric, nmr, (5) 1127
Poly(styrene), bulk polymerization, (5) 1310
equilibrium phase diagram, (5) 1310
natural rubber blend, (3) 481
Polytetramethylene oxide, (1) 19
spin-labeled, (5) 1160
Polyurethane, blends, (3) 481
block polymers, (1) 19
crystallinity, (1) 19
hard and soft domains, (1) 19
infrared dichroism, (1) 19
molecular weight, (1) 19
orientational hysteresis, (1) 19
relaxation, (1) 19
segmental orientation, (1) 19
time dependence, (1) 19
viscoelasticity, (1) 19
differential thermal analysis, (5) 1160
elastomeric, in industrial products, (2) 472
for lacquer, (2) 454
energy per strain loop, (5) 1213
in fiber-rubber composites, (2) 408
hysteresis effects of stress strain, (5) 1213
poly(butadiene) prepolymer for, (2) 456
pressure-sensitive adhesive, (2) 463
room temperature cure, (2) 472
rotational molding, (5) 1311
shear modulus, (5) 1160
temperature variation, (5) 1160
spin-labeled, (5) 1160
esr spectrum and its temperature variation of, (5) 1160
effect of strain, (5) 1160
effect of swelling, (5) 1160
stress-strain and specimen geometry, (5) 1213
Poly(vinyl chloride)-natural rubber blends, (3) 481
Powdered rubber, blending, (3) 481
energy analysis of processing, (5) 1312
starch-encased, (5) 1311
Prevulcanization inhibitors, (1) 79
Principle of corresponding states, see also Master curves, (1) 1; (2) 318
Probability density function, (5) 1116
Processability, of blends, (3) 481
of poly(butadiene), (5) 1175
of poly(isoprene), (2) 350
of polyoctenamer, (3) 511
of polypentenamer, (3) 511
Propanal, oxidation product of poly(isoprene), (5) 1094
Propane, 2-amino-2-methyl, identification by thin layer chromatography, (5) 1206
Propanesulfenic acid, 2-methyl, infrared absorption bands, (4) 949
Propane, 1,1,1-trimethylol, crosslinking agent for polyurethanes, (5) 1160
Propionaldehyde, see Propanal
Prussian blue, in determination of conjugated polyenes, (5) 1094
Pyrolysis of scrap tires, (3) 597
3-Pyrroline, 2,2,5,5-tetramethyl-1-oxyl, esr spectrum of, (5) 1160
imidazoline derivative, (5) 1160

Radial ply passenger and truck tires, hysteretic loss in, (1) 118; (2) 363
Radiation, chain scission of fluoroelastomers, (2) 282
crosslink density and dosage, (2) 282
curing by, (4) 924
curing of phosphonitrilic fluoroelastomers by, (1) 32
curing of silicone rubber, (2) 282
modulus of silicone rubber and dosage of, (2) 282
sol fraction and dosage, (2) 282
Raman spectroscopy, (4) 911
of derivatives of 2-benzothiazolethione, (4) 911
Rayon cord, adhesion to rubber and effect of oil, (1) 161
hysteretic losses in, (1) 118
Reclaim from scrap-tire material, (3) 597
Reduced modulus, (1) 1
Reinforcement by short fibers of elastomers, (5) 1074
Reinforcement, see also Carbon black
Relaxation, dielectric, (5) 1127
mechanical of various rubbers, (1) 1; (5) 1127
nuclear magnetic resonance, (5) 1127
parameters, (1) 1
of poly(isoprene), (1) 1
of polyurethane, (1) 19
Resilience, of natural rubber vulcanizates, (2) 261
of polyalkenamers, (3) 511
of poly(butadiene co styrene), (2) 279
Resorcinol-formaldehyde dips, (5) 1066
latex, (2) 436, 448, 458
Retarders, (1) 79
Reversion of vulcanization, butyl rubber, (3) 511
in natural rubber, (3) 511
in polypentenamer, (3) 511
Rhenium, compounds as catalysts for ring-opening polymerization, (3) 511
Rheology, (1) 32; (2) 333; (5) 1310
Road material from tire scrap, (3) 597
Rolling resistance of tires, effect of design, (1) 118; (2) 363
Rotational isomeric state, (5) 1116
Rotational entropy, (3) 511

Rotoflex tester, for dynamic rubber-to-metal adhesion testing, (1) 188
Rubber division, bylaws, (3) G 63
future meetings, (1) G 5; (2) G 27; (3) G 47; (4) G 83; (5) G 107
future meeting symposia, (1) G 6; (2) G 28; (3) G 48; (4) G 84; (5) G 108
guide for authors, (3) G 52; (4) G 89; (5) G 111
library and information service, (1) G 2; (2) G 24; (3) G 44; (4) G 80; (5) G 104
officers and executive committee, (1) G 1; (2) G 23; (3) G 43; (4) G 79; (5) G 103
program for the Fall meeting, (4) G 85
program for the Spring meeting, (1) G 8
steering committee, (1) G 1; (2) G 23; (3) G 43; (4) G 79; (5) G 103
weights and measures of, (4) G 100; (5) G 122
Rubber-filler bonding, heat generation and, (4) 697
mercaptopropyltrimethoxysilane and, (4) 697
and strain amplitude, (4) 697
Rubber-to-metal adhesion, (1) 171, 188
frature mechanics of, (1) 202
Rubber properties, effect on adhesion to tire cord, (1) 213

SBR, see Poly(butadiene co styrene)
Scorch inhibitors, (1) 79
Segments, crystallinity of polyurethane, (1) 19
hard and soft, (1) 19
between entanglements of rubber molecules, (1) 1; (5) 1116
Silane, bonding with, (4) 697
coupling agent, (5) 1308
for filler-rubber bonding, (4) 697
β-mercaptoethyltriethoxy, (5) 1308
γ-mercaptopropyltrimethoxy, (4) 697
Silica, aggregate, (2) 416
by-product, (5) 1308
coupling agents for, (5) 1308
deactivated fumed, (2) 429
effect on elastic modulus, (4) 765
in rubber blends, (1) 57
silane treated, (1) 32
partial replacement for carbon black, (2) 468
in poly(ethylene co propylene co diene) adhesion, (2) 458
Solubility of blends, (3) 481
Solvent resistance, of fluoroelastomers, (1) 32
of rubber blends, (1) 57
Specific heat, see Diffusivity, thermal, (4) 849
Spring, for seismic shock, (5) 1039
design, (5) 1039
distortion under load, (5) 1039
elastomeric, time-deflection curves, (5) 1039
Starch, encased, powdered rubber from, (5) 1311
xanthide reinforcement of rubber, (5) 1313
in rubber, (1) 64
Stearic acid, effect on crosslink density, (2) 266
Steel, adhesion to rubber, (1) 161, 171
Stored energy function, (4) 729
Strain amplitude, distribution in carbon balck-rubber mixture, (4) 729
effect on dynamic properties, (4) 729
and rubber-filler bonding, (4) 697
Strain, critical, in ozone resistance testing, (4) 895
Strain, simple and biaxial, (4) 788
biaxial instabilities, (4) 788
Stress birefringence, (3) 626; (5) 1234
hysteresis in, (5) 1234
Stress, critical in ozone resistance testing, (4) 895
Stress optical coefficient, dependence on crosslinking, (3) 625; (5) 1234
effect of swelling, (3) 625
of poly(isoprene), (5) 1234
temperature coefficient, (3) 625
Stress relaxation, activation energy, (5) 1241
aging and, (5) 1265
chemical, of poly(butadiene co styrene), (5) 1265
continuous, temperature effect, (5) 1265
crosslinking during, (5) 1265
effect of temperature, (5) 1265
of fiber-rubber composite, (2) 404
intermittent, (5) 1265
master curve, (1) 1
and molecular entanglement, (1) 1
and molecular weight, (1) 1
in nitrogen and air, (5) 1265
of poly(butadiene), (2) 357
of poly(butadiene co acrylonitrile), (2) 307
of poly(butadiene co styrene), (5) 1241
rate constants of, (5) 1241
silica effect, (4) 765
and temperature, (1) 1
time-temperature superposition, (2) 313
Stress strain, behavior of uncured black stock, (2) 353
in bending, (2) 377
curve of natural rubber, (2) 351
curve of natural rubber-fiber composite, (2) 400
curve of cis poly(isoprene), (2) 351
definition of terms, (5) 1213
distribution in tire, (2) 364
effect of carbon black aggregates, (2) 424
effect of temperature, (2) 353
energy dissipated during loading-unloading cycle, (5) 1213
experiment and theory compared, (3) 625
geometry of specimens for, (5) 1213
high-speed, (2) 307, 318
hysteresis effects, (5) 1213, 1234
in ideal rubber, (3) 625
isotherms, (5) 1151
of swollen vulcanizates, (5) 1151
master curve for, (2) 318, 335; (4) 778
at large deformation, (4) 788
oval geometry, (5) 1213

of poly(butadiene co acrylonitrile), (2) 307, 318
of poly(butadiene) vulcanizates, effect of cure, (2) 429
effect of carbon black graphitization, (2) 429
effect of filler loading, (2) 429
effect of carbon black structure, (2) 429
of polypentenamer vulcanizates, (3) 511
ring geometry, (5) 1213
in shear, (2) 335
in swollen rubber, (3) 625
at temperature below glass transition temperature of material, (5) 1213
uniaxial, (5) 1213
Stress softening, (4) 765
in polyurethane block polymers, (1) 19
Stress-whitening, (5) 1213
Succinaldehyde, see 1,4-Butandial
Sulfenamide, N-cyclohexyl-2-benzothiazole, (1) 79
dialkylthiocarbamyl, as accelerators of vulcanization by sulfur, (4) 906
2(4-morpholinothio) benzothiazole, (1) 79
Sulfenic acids, in rubber oxidation, (4) 949
Sulfide, bis(benzothiazolyl), Raman spectrum of, (4) 906
Sulfur, combined, (2) 266
determination of combined and free, (2) 266
effect on crosslinking efficiency of dicumyl peroxide, (2) 251, 266
kinetics of consumption of in vulcanization, (2) 254, 266
Supermolecular, flow unit, (2) 340
structure in relaxation, (1) 1
structure on surfaces of stretched film, (2) 357
Swelling and crosslink density, (4) 697
Swelling and mechanical properties, dependence of swelling equilibrium on strain, (3) 625
effect on birefringence, (3) 625
mechanism, (3) 625
torsion of cylinder, (3) 625

Tack of various rubbers, (3) 511
Tantalum, compounds as catalysts for ring-opening polymerization, (3) 511
Tearing energy, as measure of stress distribution at tip of crack, (5) 1253
of oil extended vulcanizates, (1) 127
of vulcanizates of poly(butadiene co styrene), (5) 1253
Tear strength, of poly(butadiene) vulcanizates, (5) 1175
Teleblock polymer, of poly(butadiene co styrene), (2) 461
Tetrasulfide, 2-benzothiazolyl, Raman spectrum, (4) 906
Tensile strength, effect of oil extension, (1) 127; (3) 511
of fiber-rubber composite, (2) 399
function of deformation rate, (2) 307
function of temperature, (2) 307
and hot-strip adhesion, (1) 213
of natural rubber vulcanizates, (2) 261; (4) 697; (5) 1234
of phosphonitrilic fluoroelastomer vulcanizates, (1) 32
of poly(butadiene) vulcanizates, (5) 1175
of poly(butadiene co acrylonitrile) vulcanizates, (2) 307
of poly(butadiene co styrene) vulcanizates, (2) 266; (3) 511
of poly(isoprene) vulcanizates, (2) 342
of polyoctenamer vulcanizates, (3) 511
of polypentenamer vulcanizates, (3) 511
of rubber blends, (1) 48, 57, 88
of silicone rubber vulcanizates, (2) 285
and specimen geometry, (5) 1213
of thin tubes, (4) 788
time-temperature superposition, (2) 307
Thermomechanical analysis of blends, (3) 481
Thermodynamics of rubber elasticity, anisotropic compressibility, (3) 625
contribution of internal energy to restorative force, (3) 625
intramolecular internal energy, (3) 625
significance of volume change, (3) 625
thermoelasticity in torsion, (3) 625
Thermogravimetry of rubber formulations, (5) 1193
derivative, and integral, (5) 1193
heating rate, (5) 1193
Thin tubes, stress strain of, (4) 788
theory of rubber, (4) 788
Time-temperature superposition, of stress relaxation curves, (1) 1; (2) 307
temperature reduction for time (2) 318
WLF constants for poly(butadiene co acrylonitrile), (2) 307, 318
WLF constants for poly(butadiene co styrene), (2) 333
Tin, compounds as catalysts for ring-opening polymerization, (3) 511
Tire, abrasion index, (5) 1302
bending deformation, (1) 118
blowout reistance, (5) 1302
compressive deformation, (1) 118
crack growth resistance, (5) 1302
critical deflection, (1) 118
curing, oil migration during, (1) 127
effect of oil migration on performance, (1) 127
energy loss distribution, (1) 118
fatigue, (5) 1302
flex, (5) 1302
heat generation, (2) 363; (5) 1302
analysis by analog computer, (4) 717
in cross-ply tires, (2) 363
effect of carcass compound, (2) 363
in radial-ply tires, (2) 363
response equation for, (1) 118
rolling resistance and deflection, (1) 118
and inflation, (1) 118
temperature dependence of, (1) 118
stress strain distribution, (2) 363
stress strain under load, (5) 1053
temperature distribution, (2) 363

tire test dynamometer, (2) 363
wet skid properties, (5) 1302
Tire cord, adhesion to rubber, (1) 161, 171, 213; (2) 434
adhesives (RFL) for, (5) 1066
effects of nitrogen dioxide, (5) 1066
effect of ozone, (5) 1066
compliance, (5) 1053
composite, (2) 376; (5) 1314
glass, in radial tires, (5) 1318
hysteresis, (5) 1093
moisture effect, (5) 1314
Nylon, (5) 1053
polyester, (2) 478; (5) 1314
chemical degradation, (2) 478
polyethylene terephthalate, (5) 1053
secant modulus, (5) 1053
stress relief, (5) 1053
strikethrough, (5) 1315
effect of cord concentration, (5) 1315
effect of viscosity and forming time, (5) 1315
work loss of, (5) 1053
Tire deflection, tread bending loss, (1) 118
Tire design, effect on hysteresial loss, (1) 118
Tire scrap, antiskid applications, (3) 597
artificial reefs, (3) 597
biodegradation material, (3) 597
carbon black source, (3) 597
erosion control, (3) 597
fuel, (3) 597
highway abutments, (3) 597
pyrolysis products, (3) 597
reclaim, (3) 597
retreading, (3) 597
road construction, (3) 597
roof coatings, (3) 597
sound attenuation, (3) 597
splitter industry, (3) 597
synthetic turf, (3) 597
Tire scrap preparation, (3) 597
debeading, (3) 597
pulverizing frozen tires, (3) 597
splitting, (3) 597
Tire tread, bending losses, (1) 118
Tire tread compound, fatigue life of, effect of carbon black parameters, (1) 231
Mooney-Rivlin plots, (1) 127
contribution to hysteretic losses in tires, (1) 118
Tire wear, air pollution from, (1) 150
angle abrasion index, (2) 467
carbon black properties, (2) 465, 467
dust from, (4) 1005, 1011; (5) 1275
mathematical mode for, (2) 465
severity and dust formation, (5) 1275
Trimethylolpropane trimethacrylate, curing aid for radiation curing, (4) 924
Tungsten hexachloride, catalyst for polymerization, (3) 511
cocatalysts for, (3) 511
ligand effect on, (3) 511
Tungsten, tetravalent as active species in ring-opening polymerization, (3) 511
Ultrasonic dispersion of carbon black, (4) 858
Uniaxial stretching, see also Stress-strain and Tensile strength
and formation of fibrils, (2) 361
of unfilled vulcanizates, (2) 357
Uranium alkoxides, cocatalyst for preparation of poly(butadiene), (5) 1175
Uranium, compounds for catalysts for stereoregular polymerization of butadiene, (5) 1175
removal from poly(butadiene) by washing, (5) 1175
Uranium, tetra(allyl), catalyst for preparation of poly(butadiene), (5) 1175
tri(allyl) halides, as catalysts for preparation of poly(butadiene), (5) 1175

Valency, effect on ring-opening polymerization by transition metals, (3) 511
Vinylidene fluoride copolymers, crosslink density as a function of radiation dosage, (2) 282
effect of aging on radiation vulcanizates, (2) 282
with hexafluoropropylene, (2) 282
with perfluoroalkyl vinyl ether, (2) 282
radiation crosslink and chain scission, (2) 282
sol fraction as a function of radiation dosage, (2) 282
with trifluorochloroethylene, (2) 282
Viscoelastic properties, carbon black and, (4) 729
poly(butadiene co acrylonitrile), (2) 307, 333; (4) 778
with Rheovibron, (2) 333, 363; (4) 758, 765
effects on hysteretic losses in tires, (1) 118
relationship to hysteresis, (2) 363
theory of energy loss, (2) 363
Viscoelasticity, of natural rubber, (1) 1
of poly(isoprene), (1) 1
of polyurethane, (1) 19
time, temperature, and deformation amplitude, (4) 778
Viscosity, coefficients of, (4) 825
shear-rate curves, (2) 318, 333; (4) 778
effect of silica and oil, (4) 825
power law equations for, (4) 825
relative, (4) 825
Viscous modulus, (4) 729
carbon black concentration effect, (4) 729
strain amplitude and, (4) 729
Vulcanization, see also Crosslinking
accelerators of, (4) 906
by alkylphenol-formaldehyde oligomers in open stream, (2) 409
combined sulfur in, (2) 266
dicumyl peroxide for, (2) 251, 266
efficiency, (4) 697
by electron accelerator, (4) 925
kinetics of consumption by sulfur, (2) 251
kinetics of formation of zinc sulfide, (2) 251
mechanism of, (2) 251; (4) 906
oil migration during, (1) 127

of phosphonitrilic fluoroelastomers, (1) 32
of polyalkenamers, (3) 511
retardation by N-cyclohexylthio-o-sulfimide, (1) 79
by radiation, (2) 282, 285
of silicone rubber, (2) 285
by sulfur, acceleration by dialkylthiocarbamyl sulfenamides, (4) 906
of vinylidene fluoride copolymers, (2) 282

Weibull statistics for fatigue data, (1) 188, 231

X-ray analysis of rubber blends, (3) 481

Yield stress and strain, (5) 1213

Zinc analysis, as measure of tire dust, (5) 1275
Zinc dimethyldithiocarbamate, in vulcanization of natural rubber by nitrosophenols and diisocyanates, (1) 100
Zinc oxide, crosslink density and, (2) 251
effect in rubber of various, (5) 1318
effect on vulcanization mechanism, (2) 251, 266
manufacture effect of, (5) 1318
particle size, (5) 1318
pelletization, (5) 1318
Zinc salt of MBT, Raman spectrum of, (4) 906
Zinc sulfide, kinetics of formation in vulcanization, (2) 251